

Your calibration kit has been designed to withstand a moderate amount of physical stress. However, to retain its high precision performance you should treat it with care and prevent any mechanical shock.

It can be damaged if excessive force is applied to the connectors. Such a damage is considered as an abuse of the cal kit and will void the warranty when verified by our service professionals. When the kit is not in use, mount protective caps on the connectors such as the ones which came with the kit.

Store the kit in a shock-resistant environment.

Tighten 3.5 mm connectors with a torque wrench. Torque: 8 lb-inch (90 N-cm)

For information on service and recertification go to

<http://www.keysight.com/find/serviceprices>

Temperature loading	operating temperature range	+18 °C to +28 °C
	storage temperature range	-40 °C to +70 °C, in line with EN 60068-2-1 and EN 60068-2-2
Recommended inspection interval		1 year



85520-90001



Data Sheet

85520A

Cal Kit

Type-3.5mm(m) 50 Ω

DC to 26.5 GHz

Subject to change

Issue: A

Date: 03.06.2014

www.valuetronics.com

Standard	Electrical Delay
Through	
male-male	115.888 ps

Standard	Offset Delay
Open	
male	30.765 ps

Standard	Offset Delay
Short	
male	30.508 ps

Standard	DC-Resistance
Load	
male	50 Ω \pm 0.5 Ω

Standard	Return Loss (typical)	
Through	DC to 5 GHz	5 to 26.5 GHz
male-male	\geq 34 dB	\geq 30 dB

Standard	C_0 E-15 F	C_1 E-27 F/Hz	C_2 E-36 F/Hz ²	C_3 E-45 F/Hz ³
Open				
male	-0.11	6	-4.39	0.179

Standard	L_0 E-12 H	L_1 E-24 H/Hz	L_2 E-33 H/Hz ²	L_3 E-42 H/Hz ³
Short				
male	4.645	-331	10.8	-0.12

Standard	Return Loss (spec)		
Load	DC to 5 GHz	5 to 15 GHz	15 to 26.5 GHz
male	\geq 42 dB	\geq 36 dB	\geq 32 dB

Standard	Insertion Loss (typical)
Through	0 to 26.5 GHz
male-male	\leq 0.035 dB x sqrt (f/GHz)

Standard	Deviation from Nominal Phase (spec)		
Open	DC to 5 GHz	5 to 15 GHz	15 to 26.5 GHz
male	\leq 1.5°	\leq 3.0°	\leq 4.5°

Standard	Deviation from Nominal Phase (spec)		
Short	DC to 5 GHz	5 to 15 GHz	15 to 26.5 GHz
male	\leq 1.0°	\leq 2.5°	\leq 4.0°

Standard	Max. Power
Load	
male	0.25 W