

DC Voltage/Current Generators/Calibrators

Low-Output, High-Precision Working Standard VIG

R6161

Specifications

DC Voltage/Current Output

Generation range:

Range	Generating range	Minimum step
10 mV (Divider on)	0 to ± 11.99999 mV	10 nV
100 mV (Divider on)	0 to ± 119.9999 mV	100 nV
1000 mV (Divider on)	0 to ± 1199.999 mV	1 μ V
1 V	0 to ± 1.999999 V	1 μ V
10 V	0 to ± 11.999999 V	10 μ V
100 V	0 to ± 119.99999 V	100 μ V
1000 V	0 to ± 1199.9999 V	1 mV
1 mA	0 to ± 1.999999 V	1 nA
10 mA	0 to ± 11.999999 V	10 nA
100 mA	0 to ± 119.99999 V	100 nA

Overall accuracy: Includes the external standard, traceability, calibration error, stability, temperature coefficient, change over time, linearity, noise and ripple (excluding line regulation and load regulation).

The temperature is $23^{\circ}\text{C} \pm 5^{\circ}\text{C}$ and the relative humidity is less than 70%. The preheating time must be one hour or more.

*The current range is guaranteed at the follow-up voltage ± 10 V or less.

24-hour total accuracy

Range	Error	Setting error		Range error
10 mV (Divider on)		$\pm 0.0055\%$	+	± 0.7 μ V
100 mV (Divider on)		$\pm 0.0040\%$	+	± 0.8 μ V
1000 mV (Divider on)		$\pm 0.0030\%$	+	± 6 μ V
1 V		$\pm 0.0020\%$	+	± 10 μ V
10 V		$\pm 0.0020\%$	+	± 60 μ V
100 V		$\pm 0.0020\%$	+	± 600 μ V
1000 V		$\pm 0.0025\%$	+	± 6 mV
1 mA		$\pm 0.0055\%$	+	± 9 nA
10 mA		$\pm 0.0040\%$	+	± 90 nA
100 mA		$\pm 0.0040\%$	+	± 900 nA

90-day total accuracy

Range	Error	Setting error		Range error
10 mV (Divider on)		$\pm 0.0060\%$	+	± 2.3 μ V
100 mV (Divider on)		$\pm 0.0045\%$	+	± 2.5 μ V
1000 mV (Divider on)		$\pm 0.0035\%$	+	± 8 μ V
1 V		$\pm 0.0025\%$	+	± 11 μ V
10 V		$\pm 0.0025\%$	+	± 70 μ V
100 V		$\pm 0.0025\%$	+	± 700 μ V
1000 V		$\pm 0.0030\%$	+	± 7 mV
1 mA		$\pm 0.0060\%$	+	± 9 nA
10 mA		$\pm 0.0045\%$	+	± 90 nA
100 mA		$\pm 0.0045\%$	+	± 900 nA

Relative accuracy: A value indicating overall accuracy except for external standard traceability. Includes the calibration error, stability, temperature coefficient, change over time, linearity, noise and ripple, (DC to 1 Hz). (Excludes line regulation and load regulation)

The temperature is $23^{\circ}\text{C} \pm 1^{\circ}\text{C}$ and the relative humidity is less than 70%. The preheating time must be one hour or more.

24-hour relative accuracy:

Range	Error	Setting error		Range error
10 mV (Divider on)		$\pm 0.0010\%$	+	± 0.5 μ V
100 mV (Divider on)		$\pm 0.0010\%$	+	± 0.5 μ V
1000 mV (Divider on)		$\pm 0.0010\%$	+	± 4 μ V
1 V		$\pm 0.0005\%$	+	± 6 μ V
10 V		$\pm 0.0005\%$	+	± 40 μ V
100 V		$\pm 0.0005\%$	+	± 400 μ V
1000 V		$\pm 0.0008\%$	+	± 4 mV
1 mA		$\pm 0.0015\%$	+	± 5 nA
10 mA		$\pm 0.0010\%$	+	± 50 nA
100 mA		$\pm 0.0010\%$	+	± 500 nA

90-day relative accuracy:

Range	Error	Setting error		Range error
10 mV (Divider on)		$\pm 0.0020\%$	+	± 2 μ V
100 mV (Divider on)		$\pm 0.0020\%$	+	± 2 μ V
1000 mV (Divider on)		$\pm 0.0020\%$	+	± 6 μ V
1 V		$\pm 0.0015\%$	+	± 8 μ V
10 V		$\pm 0.0015\%$	+	± 50 μ V
100 V		$\pm 0.0015\%$	+	± 500 μ V
1000 V		$\pm 0.0015\%$	+	± 5 mV
1 mA		$\pm 0.0025\%$	+	± 6 nA
10 mA		$\pm 0.0020\%$	+	± 60 nA
100 mA		$\pm 0.0020\%$	+	± 600 nA

One day stability: The temperature is $23^{\circ}\text{C} \pm 1^{\circ}\text{C}$ and the relative humidity is 70% or less. The preheating time must be one hour or more. The power and load conditions following that must be constant.

*The current range is guaranteed at the follow-up voltage ± 10 V or less.

Range	Error	Setting error		Range error
10 mV (Divider on)		$\pm 0.0007\%$	+	± 0.3 μ V
100 mV (Divider on)		$\pm 0.0007\%$	+	± 0.3 μ V
1000 mV (Divider on)		$\pm 0.0007\%$	+	± 2 μ V
1 V		$\pm 0.0005\%$	+	± 3 μ V
10 V		$\pm 0.0005\%$	+	± 20 μ V
100 V		$\pm 0.0005\%$	+	± 200 μ V
1000 V		$\pm 0.0005\%$	+	± 2 mV
1 mA		$\pm 0.0012\%$	+	± 2 nA
10 mA		$\pm 0.0007\%$	+	± 20 nA
100 mA		$\pm 0.0007\%$	+	± 200 nA

Temperature coefficient: The temperature is $23^{\circ}\text{C} \pm 10^{\circ}\text{C}$ and the relative humidity is 70% or less. The preheating time must be one hour or more. The power and load conditions following that must be constant.

Range	Error	Setting error		Range error
10 mV (Divider on)		$\pm 0.0004/^{\circ}\text{C}$	+	± 0.01 $\mu\text{V}/^{\circ}\text{C}$
100 mV (Divider on)		$\pm 0.0004/^{\circ}\text{C}$	+	± 0.07 $\mu\text{V}/^{\circ}\text{C}$
1000 mV (Divider on)		$\pm 0.0004/^{\circ}\text{C}$	+	± 0.6 $\mu\text{V}/^{\circ}\text{C}$
1 V		$\pm 0.0002/^{\circ}\text{C}$	+	± 1 $\mu\text{V}/^{\circ}\text{C}$
10 V		$\pm 0.0002/^{\circ}\text{C}$	+	± 6 $\mu\text{V}/^{\circ}\text{C}$
100 V		$\pm 0.0002/^{\circ}\text{C}$	+	± 60 $\mu\text{V}/^{\circ}\text{C}$
1000 V		$\pm 0.0003/^{\circ}\text{C}$	+	± 600 $\mu\text{V}/^{\circ}\text{C}$
1 mA		$\pm 0.0006/^{\circ}\text{C}$	+	± 0.7 nA/ $^{\circ}\text{C}$
10 mA		$\pm 0.0004/^{\circ}\text{C}$	+	± 7 nA/ $^{\circ}\text{C}$
100 mA		$\pm 0.0004/^{\circ}\text{C}$	+	± 70 nA/ $^{\circ}\text{C}$

DC Voltage/Current Generators/Calibrators

Low-Output, High-Precision Working Standard VIG

R6161 (Continued From Previous Page)

Linearity: The temperature is $23^{\circ}\text{C} \pm 1^{\circ}\text{C}$ and the relative humidity is 70% or less. The preheating time must be one hour or more. The power and load conditions following that must be constant. The current range is at follow-up voltage $\pm 10\text{ V}$ or less.

Range	Linearity Error
10 mV (Divider on)	$\pm 0.03\ \mu\text{V}$
100 mV (Divider on)	$\pm 0.3\ \mu\text{V}$
1000 mV (Divider on)	$\pm 4\ \mu\text{V}$
1 V	$\pm 3\ \mu\text{V}$
10 V	$\pm 30\ \mu\text{V}$
100 V	$\pm 400\ \mu\text{V}$
1000 V	$\pm 5\text{ mV}$
1 mA	$\pm 3\text{ nA}$
10 mA	$\pm 30\text{ nA}$
100 mA	$\pm 500\text{ nA}$

Noise and ripple: Current range for a 1 k Ω load resistance

Range	0.1 Hz to 10 Hz (rms)	10 Hz to 10 kHz (rms)	DC to 20 MHz (p-p)
10 mV (Divider on)	$\pm 0.2\ \mu\text{V}$	20 μV	1 mV
100 mV (Divider on)	$\pm 0.5\ \mu\text{V}$	20 μV	1 mV
1000 mV (Divider on)	$\pm 1\ \mu\text{V}$	20 μV	1 mV
1 V	$\pm 2\ \mu\text{V}$	100 μV	3 mV
10 V	$\pm 10\ \mu\text{V}$	100 μV	3 mV
100 V	$\pm 100\ \mu\text{V}$	100 μV	3 mV
1000 V	$\pm 1\text{ mV}$	1 mV	10 mV
1 mA	$\pm 5\text{ nA}$	50 nA	2 μA (10 μA)*
10 mA	$\pm 20\text{ nA}$	200 nA	2 μA (10 μA)*
100 mA	$\pm 200\text{ nA}$	500 nA	10 μA

* The values in parentheses are for the 1 mA and 10 mA ranges of option 01.

Load regulation and output resistance:

Range	Load regulation (load condition)	Output resistance*
10 mV (Divider on)		200 $\Omega \pm 0.5\%$
100 mV (Divider on)		200 $\Omega \pm 0.5\%$
1000 mV (Divider on)		200 $\Omega \pm 0.5\%$
1 V	$\pm 0.0008\%$ (10 Ω or more)	100 m Ω or less
10 V	$\pm 0.0002\%$ (100 Ω or more)	100 m Ω or less
100 V	$\pm 0.0002\%$ (1 k Ω or more)	100 m Ω or less
1000 V	$\pm 0.0002\%$ (100 k Ω or more)	100 m Ω or less
1 mA	$\pm 0.0002\%$ (10 k Ω or more)	5 G Ω or more
10 mA	$\pm 0.0002\%$ (1 k Ω or more)	5 G Ω or more
100 mA	$\pm 0.0002\%$ (100 Ω or more)	1 G Ω or more

* Output resistance at EXT.SENSE "OFF" (during two-wire connection) output pin

Settling time: Arrival time to $\pm 0.001\%$ of last value (The 100 mA range is the arrival time to $\pm 0.0015\%$ of last value.)

Range	Settling time	Load condition
10 mV (Divider on)	1 s	
100 mV (Divider on)	1 s	
1000 mV (Divider on)	1 s	
1 V	1 s	
10 V	1 s	
100 V	1 s	
1000 V	10 s*	
1 mA	1 s	100 k Ω or less
10 mA	1 s	10 k Ω or less
100 mA	1 s	1 k Ω or less

* In the 1000 V range, the arrival time to $\pm 0.05\%$ of last value is within 3 sec. In the 1 mA and 10 mA ranges of option 01, the arrival time to $\pm 0.005\%$ of the last value is within 5 sec. (The load conditions are 1 M Ω or less and 100 k Ω or less, respectively.)

DC Voltage Output

Maximum output current: 1 V, 10 V, and 100 V ranges; 120 mA and 1000 V ranges; 12 mA

Range	Maximum output current
1 V	$\pm 120\text{ mA}$
10 V	$\pm 120\text{ mA}$
100 V	$\pm 120\text{ mA}$
1000 V	$\pm 12\text{ mA}$

Preheating time (Time required until reaching the specified accuracy): One hour or more

Common mode noise elimination ratio: 140 dB or more (DC) and 80 dB or more (50/60 Hz $\pm 1\%$) with 1 k Ω unbalanced impedance between the -OUTPUT/-SENSE pin and guard pin

DC Current Output

Range	Maximum follow-up voltage
1 mA	$\pm 120\text{ V}$
10 mA	$\pm 120\text{ V}$
100 mA	$\pm 120\text{ V}$

Maximum follow-up voltage: 120 V, 1200 V is possible in the 1 mA and 10 mA ranges of option 01.

Input/Output Functions

Remote control (BCD) function: Can control the voltage generation, current generation output value, range, polarity, voltage limit, current limit and other parameters in parallel.

GPIO interface: Conforms to IEEE STD 488-1978.

(SH1, AH1, T6, L3, SR1, RL1, PRO, DC1, DT1, CO, and E2)

General Specifications

Voltage limiter setting: 10 V to 1250 V (resolution of 10 V)

Current limiter setting: 1 mA to 125 mA (resolution of 1 mA)

Maximum applied voltage between terminals:

Between guard terminal and chassis terminal $\pm 500\text{ V}$ peak

Between -OUTPUT/-SENSE terminal and guard terminal $\pm 50\text{ V}$ peak

Between +OUTPUT/+SENSE terminal and guard terminal $\pm 1250\text{ V}$ peak

Between OUTPUT terminal and SENSE terminal $\pm 1\text{ V}$ peak

Output format: Floating, unipolar output

Continuous variable unit: The high-order digits can be continuously changed from any digit.

Internal program memory: 100 steps (The step time is 1 to 99 sec. The accuracy is within 7% of the set time.)

Program recall mode Can be set to random step, single scan, repeat scan, first channel and last channel

Single-wire signal: Trigger input; Starts program operation

Operating conditions: 0°C to $+40^{\circ}\text{C}$, relative humidity 70% or less (0°C to $+35^{\circ}\text{C}$, relative humidity 85% or less)

Storage temperature range: -25°C to $+70^{\circ}\text{C}$

Display: Seven-segment green LED digit display. Only a negative (-) polarity is displayed.

Power requirements: Specify at time of ordering

Option No.	Standard	32	42	44
Supply voltage (V)	90 to 110	103 to 132	198 to 242	207 to 250

Frequency: 48 to 66 Hz

Power consumption: 110 VA or less

Dimensions/Mass: Approx. 424 (W) \times 132 (H) \times 450 (D) mm/17.5kg or less

Standard Accessories

A01402 Power cables (one of each)

Options

Option 01 (Can change the maximum follow-up voltage in the 1 mA and 10 mA ranges to 1200 V.)

Accessories (Sold separately)

A02708 Rack mount set A (EIA standard, including a front handle)

A02709 Rack mount set A (JIS standard, including a front handle)

A02718 Rack mount set B (EIA standard, excluding a front handle)

A02719 Rack mount set B (JIS standard, excluding a front handle)