

Agilent 35670A Dynamic Signal Analyzer

Versatile two- or four-channel high-performance
FFT-based spectrum/network analyzer
122 μ Hz to 102.4 kHz 16-bit ADC

Data Sheet



Key Specifications

Frequency range	102.4 kHz 1 channel 51.2 kHz 2 channel 25.6 kHz 4 channel
Dynamic range	90 dB typical
Accuracy	± 0.15 dB
Channel match	± 0.04 dB and ± 0.5 degrees
Real-time bandwidth	25.6 kHz/1 channel
Resolution	100, 200, 400, 800 & 1600 lines
Time capture	> 6 Msamples
Source types	Random, burst random, periodic chirp, burst chirp, pink noise, sine, swept-sine (Option1D2), arbitrary (Option 1D4)



Agilent Technologies

Summary of Features on Standard Instrument

The following features are standard with the Agilent 35670A:

Instrument modes

FFT analysis	Histogram/time
Correlation analysis	Time capture

Measurement

Frequency domain	
Frequency response	Power spectrum
Linear spectrum	Coherence
Cross spectrum	Power spectral density

Time domain (oscilloscope mode)

Time waveform	Autocorrelation
Cross-correlation	Orbit diagram
Amplitude domain	
Histogram, PDF, CDF	

Trace coordinates

Linear magnitude	Unwrapped phase
Log magnitude	Real part
dB magnitude	Imaginary part
Group delay	Nyquist diagram
Phase	Polar

Trace units

Y-axis amplitude: combinations of units, unit value, calculated value, and unit format describe y-axis amplitude

Units: volts, g, meters/sec², inches/sec², meters/sec, inches/sec, meters, mils, inches, pascals, Kg, N, dyn, lb, user-defined EUs

Unit value: rms, peak, peak-to-peak

Calculated value: V, V², V²/Hz, √Hz, V²s/Hz (ESD)

Unit format: linear, dB's with user selectable dB reference, dBm with user selectable impedance.

Y-axis phase: degrees, radians

X-axis: Hz, cpm, order, seconds, user-defined

Display formats

- Single
- Quad
- Dual upper/lower traces
- Small upper and largelower
- Front/back overlay traces
- Measurement state
- Bode diagram
- Waterfall display with skew, -45 to 45 degrees
- Trace grids on/off
- Display blanking
- Screen saver

Display scaling

Autoscale	Selectable reference
Manual Scale	Linear or log X-axis
Input range tracking	Y-axis log
X & Y scale markers with expand and scroll	

Marker functions

- Individual trace markers
- Coupled multi-trace markers
- Absolute or relative marker
- Peak search
- Harmonic markers
- Band marker
- Sideband power markers
- Waterfall markers
- Time parameter markers
- Frequency response markers

Signal averaging (FFT mode)

Average types (1 to 9,999,999 averages)	
RMS	Time exponential
RMS exponential	Peak hold
Time	

Averaging controls

- Overload reject
- Fast averaging on/off
- Update rate select
- Select overlap process percentage
- Preview time record

Measurement control

- Start measurement
- Pause/continue measurement

Triggering

- Continuous (Freerun)
- External (analog or TTL level)
- Internal trigger from any channel
- Source synchronized trigger
- GPIB trigger
- Armed triggers
- Automatic/manual
- RPM step
- Time step
- Pre- and post-trigger measurement Delay

Tachometer input:

- ±4 V or ±20 V range
- 40 mv or 200 mV resolution
- Up to 2048 pulses/rev
- Tach hold-off control

Source outputs

Random	Burst random
Periodic chirp	Burst chirp
Pink noise	Fixed sine

Note: Some source types are not available for use in optional modes. See option description for details.

Input channels

Manual range	Anti-alias filters On/Off
Up-only auto range	AC or DC coupling
Up/down auto range	LED half range and overload indicators
Floating or grounded	A-weight filters On/Off
Transducer power supplies (4 ma constant current)	

Frequency

20 spans from 195 mHz to 102.4 kHz (1 channel mode)
20 spans from 98 mHz to 51.2 kHz (2 channel mode)
Digital zoom with 244 μ Hz resolution throughout the 102.4 kHz frequency bands.

Resolution

100, 200, 400, 800 and 1600 lines

Windows

Hann	Uniform
Flat top	Force/exponential

Math

+,-,*, /	Conjugate
Magnitude	Real and imaginary
Square Root	FFT, FFT ⁻¹
LN	EXP
*j ω or /j ω	PSD
Differentiation	A, B, and C weighting
Integration	Constants K1 thru K5 Functions F1 thru F5

Analysis

Limit test with pass/fail
Data table with tabular readout
Data editing

Time capture functions

Capture transient events for repeated analysis in FFT, octave, order, histogram, or correlation modes (except swept-sine). Time-captured data may be saved to internal or external disk, or transferred over GPIB. Zoom on captured data for detailed narrowband analysis.

Data storage functions

Built-in 3.5 in., 1.44-Mbyte flexible disk also supports 720-KByte disks, and 2 Mbyte NVRAM disk. Both MS-DOS[®] and HP-LIF formats are available. Data can be formatted as either ASCII or binary (SDF). The 35670A provides storage and recall from the internal disk, internal RAM disk, internal NVRAM disk, or external GPIB disk for any of the following information:

Instrument setup states	Trace data
User-math	Limit data
Time capture buffers	Agilent Instrument BASIC Programs
Waterfall display data	Curve fit/synthesis tables
Data tables	

GPIB capabilities

Conforms to IEEE 488.1/488.2
Conforms to SCPI 1992
Controller with Agilent Instrument Basic Option

Calibration & memory

Single or automatic calibration
Built-in diagnostics & service tests
Nonvolatile clock with time/date
Time/date stamp on plots and saved data files

Online help

Access to topics via keyboard or index

Fan

On/Off

Agilent 35670A Specifications

Instrument specifications apply after 15 minutes warm-up and within 2 hours of the last self-calibration. When the internal cooling fan has been turned OFF, specifications apply within 5 minutes of the last self-calibration. All specifications are with 400 line frequency resolution and with anti-alias filters enabled unless stated otherwise.

Frequency

Maximum range**

1 channel mode	102.4 kHz, 51.2 kHz (opt AY6*)
2 channel mode	51.2 kHz
4 channel mode (Option AY6 only)	25.6 kHz

Spans

1 channel mode	195.3 mHz to 102.4 kHz
2 channel mode	97.7 mHz to 51.2 kHz
4 channel mode (Option AY6 only)	97.7 mHz to 25.6 kHz

Minimum resolution

1 channel mode	122 μ Hz (1600 line display)
2 channel mode	61 μ Hz (1600 line display)
4 channel mode (Option AY6 only)	122 μ Hz (800 line display)

Maximum real-time bandwidth

FFT span for continuous data acquisition)
(Preset, fast averaging)

1 channel mode	25.6 kHz
2 channel mode	12.8 kHz
4 channel mode (Option AY6 only)	6.4 kHz

Measurement rate

(Typical) (Preset, fast averaging)

1 channel mode	≥ 70 averages/sec
2 channel mode	≥ 33 averages/sec
4 channel mode (Option AY6 only)	≥ 15 averages/sec

Display update rate

Typical (Preset, fast average off)	≥ 5 updates/Sec
Maximum	≥ 9 updates/Sec

(Preset, fast average off, single channel, single display, undisplayed trace displays set to data registers)

Accuracy

± 30 ppm (.003%)

Single channel amplitude

Absolute amplitude accuracy (FFT)

(A combination of full scale accuracy, full scale flatness, and amplitude linearity.)

$\pm 2.92\%$ (0.25 dB) of reading

$\pm 0.025\%$ of full scale

FFT full scale accuracy at 1 kHz (0 dBfs)

± 0.15 dB (1.74%)

FFT full scale flatness (0 dBfs) relative to 1 kHz

± 0.2 dB (2.33%)

FFT amplitude linearity at 1 kHz measured on +27 dBVrms range with time avg, 0 to -80 dBfs

$\pm 0.58\%$ (0.05 dB) of reading

$\pm 0.025\%$ of full scale

Amplitude resolution

(16 bits less 2 dB over-range) with averaging 0.0019% of full scale (typical)

Residual DC response (FFT mode)

Frequency display (excludes A-weight filter)

<-30 dBfs or 0.5 mVdc

FFT dynamic range

Spurious free dynamic range

(Includes spurs, harmonic distortion, intermodulation distortion, alias products). Excludes alias responses at extremes of span.

Source impedance = 50 Ω .

800 line display.

90 dB typical (<-80 dBfs)


* Option AY6 single channel maximum range extends to 102.4 kHz without anti-alias filter protection.

** Show all lines mode allows display of up to 131.1, 65.5 and 32.7 kHz respectively. Amplitudes accuracy is unspecified and not alias protected.

Full span FFT noise floor (typical)

Flat top window, 64 RMS averages, 800 line display.

Typical noise floor vs. range for different frequency spans



Harmonic distortion	<-80 dBfs
Single Tone (in band), ≤ 0 dBfs	
Intermodulation distortion	<-80 dBfs
Two tones (in-band), each ≤ -6.02 dBfs	
Spurious and residual responses	<-80 dBfs
Source impedance = 50 Ω .	
Frequency alias responses	
Single tone (out of displayed range), ≤ 0 dBfs, ≤ 1 MHz	
(≤ 200 kHz with IEPE transducer power supply On)	
2.5% to 97.5% of the frequency span	<-80 dBfs
Lower and upper 2.5% of frequency span	<-65 dBfs

Input noise

Input noise level

Flat top window, -51 dBVrms range

Source impedance = 50 Ω

Above 1280 Hz <-140 dBVrms/ $\sqrt{2}$ Hz

160 Hz to 1280 Hz <-130 dBVrms/ $\sqrt{2}$ Hz

Note: To calculate noise as dB below full scale:

Noise [dBfs] = Noise [dB/ $\sqrt{2}$ Hz] + 10LOG(NBW) - Range [dBVrms]; where NBW is the noise equivalent BW of the window (see below).

Window parameters	Uniform	Hann	Flat top
-3 dB bandwidth*	0.125% of span	0.185% of span	0.450% of span
Noise equivalent bandwidth*	0.125% of span	0.1875% of span	0.4775% of span
Attenuation at $\pm 1/2$ bin	4.0 dB	1.5 dB	0.01 dB
Shape factor	716	9.1	2.6
(-60 dB BW/-3 dB BW)			

* For 800 line displays. With 1600, 400, 200, or 100 line displays, multiply bandwidths by 0.5, 2, 4, and 8, respectively.

Single channel phase

Phase accuracy relative to external trigger ± 4.0 deg

16 time averages center of bin,
DC coupled 0 dBfs to -50 dBfs only
0 Hz < freq \leq 10.24 kHz only

For Hann and flat top windows, phase is relative to a cosine wave at the center of the time record. For the uniform, force, and exponential windows, phase is relative to a cosine wave at the beginning of the time record.

Cross-channel amplitude

FFT cross-channel gain accuracy ± 0.04 dB (0.46%)

Frequency response mode
Same amplitude range
At full scale: Tested with 10 RMS averages on the -11 to +27 dBVrms ranges, and 100 RMS averages on the -51 dBVrms range

Cross-channel phase

Cross-channel phase accuracy ± 0.5 deg

(Same conditions as cross-channel amplitude)

Input

Input ranges (full scale)

(Auto-range capability)

+27 dBVrms (31.7 Vpk) to -51 dBVrms
(3.99 mVpk) in 2 dB steps

Maximum input levels 42 Vpk

Input impedance 1 M Ω \pm 10%

90 μ F nominal

Low side to chassis impedance 1 M Ω \pm 30% (typical)

Floating mode <0.010 μ F

Grounded mode \leq 100 Ω

AC coupling rolloff <3 dB rolloff at 1 Hz

Source impedance = 50 Ω

Common mode rejection ratio

Single tone at or below 1 kHz

-51 dBVrms to -11 dBVrms ranges >75 dB typical

-9 dBVrms to +9 dBVrms ranges >60 dB typical

+11 dBVrms to +27 dBVrms ranges >50 dB typical

Common mode range

(floating mode) ± 4 V pk

IEPE transducer power supply

Current source 4.25 \pm 1.5 mA

Open circuit voltage +26 to +32 Vdc

A-weight filter

Type 0 tolerance

Conforms to ANSI Standard S1.4-1983;
and to IEC 651-1979; 10 Hz to 25.6 kHz

Crosstalk

Between input channels, and
source-to-input (Receiving channel
source impedance = 50 Ω) < -135 dB
below signal or
< -80 dBfs of
receiving
channel, which-
ever response
is greater in
amplitude

Time domain

Specifications apply in histogram/time mode,
and unfiltered time display

DC amplitude accuracy ± 5.0 %fs

Rise time of -1 V to 0 V test pulse <11.4 μ Sec

Settling time of -1 V to 0 V test pulse <16 μ Sec to 1%

**Peak overshoot of -1 V to 0 V
test pulse** <3%

Sampling period

1 channel mode 3.815 μ Sec to 2 Sec in 2x steps

2 channel mode 7.629 μ Sec to 4 Sec in 2x steps

4 channel mode 15.26 μ Sec to 8 Sec in 2x steps

(Option AY6 only)

Trigger

Trigger modes	Internal, source, external (analog setting) GPIB
Maximum trigger delay	
Post trigger	8191 seconds
Pre trigger	8191 sample periods
No two channels can be further than ± 7168 samples from each other.	
External trigger max. input	± 42 Vpk
External trigger range	
Low range	-2 V to +2 V
High range	-10 V to +10 V
External trigger resolution	
Low range	15.7 mV
High range	78 mV

Tachometer

Pulses per Revolution	0.5 to 2048
RPM	$5 \leq \text{RPM} \leq 491,519$
RPM Accuracy	± 100 ppm (0.01%) (typical)
Tach level range	
Low range	-4 V to +4 V
High range	-20 V to +20 V
Tach level resolution	
Low range	39 mV
High range	197 mV
Maximum tach input level	± 42 Vpk
Minimum tach pulse width	600 nSec
Maximum tach pulse rate	400 kHz (typical)

Source output

Source types	Sine, random noise, chirp, pink noise, burst random, burst chirp
Amplitude range	AC: ± 5 V peak* DC: ± 10 V* <i>* $V_{ac_{pk}} + V_{dc} \leq 10$ V</i>
AC amplitude resolution	
Voltage > 0.2 Vrms	2.5 mVpeak
Voltage < 0.2 Vrms	0.25 mVpeak
DC offset accuracy	± 15 mV $\pm 3\%$ of ($ DC + V_{ac_{pk}}$) settings
Pink noise adder	Add 600 mV typical when using pink noise
Output impedance	< 5 Ω
Maximum loading	
Current	± 20 mA peak
Capacitance	0.01 μ F
Sine amplitude accuracy at 1 kHz	$\pm 4\%$ (0.34 dB) of setting
Rload > 250 Ω	0.1 Vpk to 5 Vpk
Sine Flatness (relative to 1 kHz)	± 1 dB 0.1 V to 5 V peak
Harmonic and sub-harmonic distortion and spurious signals (In band)	0.1 Vpk to 5 Vpk sine wave
Fundamental < 30 kHz	< -60 dBc
Fundamental > 30 kHz	< -40 dBc

Digital interfaces

External keyboard	Compatible with PC-style 101-key keyboard
--------------------------	-------------------------------------------

GPIB

Conforms to the following standards:
IEEE 488.1 (SH1, AH1, T6, TE0, L4, LE0, SR1, RL1, PP0, DC1, DT1, C1, C2, C3, C12, E2)
EEE 488.2-1987

Complies with SCPI 1992

Data transfer rate (REAL 64 Format)	< 45 mSec for a 401 point trace
Serial port	
Parallel port	
External VGA port	

Computed order tracking – Option 1D0

$$\left(\frac{\text{Maximum order} \times \text{Maximum RPM}}{60} \right) \leq$$

Online (real time)	1 channel mode	25,600 Hz
	2 channel mode	12,800 Hz
	4 channel mode	6,400 Hz
Capture playback	1 channel mode	102,400 Hz
	2 channel mode	51,200 Hz
	4 channel mode	25,600 Hz
Number of orders ≤ 200	5 ≤ RPM ≤ 491,519 (Maximum useable RPM is limited by resolution, tach pulse rate, pulses/revolution and average mode settings.)	
Delta order	1/128 to 1/1	
Resolution	≤ 400 (Maximum order)/(Delta order)	
Maximum RPM ramp rate	1000 RPM/second real-time (typical)	
1000 - 10,000 RPM run up		
Maximum order	10	
Delta order	0.1	
RPM step	30 (1 channel) 60 (2 channel) 120 (4 channel)	
Order track amplitude accuracy	±1 dB (typical)	

Real time octave analysis – Option 1D1

Standards

Conforms to ANSI Standard S1.11 - 1986, Order 3, Type 1-D, extended and optional frequency ranges
Conforms to IEC 651-1979 Type 0 Impulse, and ANSI S1.4

1 second stable average

Single tone at band center: ≤ ± 0.20 dB

Readings are taken from the linear total power spectrum bin. It is derived from sum of each filter.

1/3-octave dynamic range > 80 dB (typical) per ANSI S1.11-1986

2 second stable average

Total power limited by input noise level

Frequency ranges (at centers)

Online (real time):

	Single channel	2 channel	4 channel
1/1 octave	0.063 - 16 kHz	0.063 - 8 kHz	0.063 - 4 kHz
1/3 octave	0.08 - 40 kHz	0.08 - 20 kHz	0.08 - 10 kHz
1/12 octave	0.0997 - 12.338 kHz	0.0997 - 6.169 kHz	0.0997 - 3.084 kHz

Capture playback

1/1 octave	0.063 - 16 kHz	0.063 - 16 kHz	0.063 - 16 kHz
1/3 octave	0.08 - 31.5 kHz	0.08 - 31.5 kHz	0.08 - 31.5 kHz
1/12 octave	0.0997 - 49.35 kHz	0.0997 - 49.35 kHz	0.0997 - 49.35 kHz

One to 12 octaves can be measured and displayed.

1/1-, 1/3-, and 1/12-octave true center frequencies related by the formula: $f(i+1)/f(i) = 2^{(1/n)}$; $n=1, 3, \text{ or } 12$; where 1000 Hz is the reference for 1/1, 1/3 octave, and $1000 \times 2^{(1/24)}$ Hz is the reference for 1/12 octave. The marker returns the ANSI standard preferred frequencies.

Swept sine measurements – Option 1D2

Dynamic range 130 dB

Tested with 11 dBVrms source level at: 100 mSec integration

Curve fit/synthesis – Option 1D3

20 Poles/20 zeroes curve filter frequency response
synthesis pole/zero, pole residue & polynomial format

Arbitrary waveform source – Option 1D4

Amplitude range AC: ±5 V peak*

DC: ±10 V*

* $V_{ac, pk} + |V_{dc}| \leq 10 \text{ V}$

Record length # of points = 2.56 x lines of resolution, or # of complex points = 1.28 x lines of resolution

DAC resolution

0.2828 Vpk to 5 Vpk 2.5 mV

0 Vpk to 0.2828 Vpk 0.25 mV

General Specifications

General specifications

Safety standards CSA certified for electronic test and measurement equipment per CSA C22.2, NO. 231 This product is designed for compliance to: UL1244, Fourth Edition IEC 348, 2nd Edition, 1978

EMI / RFI standards CISPR 11

Acoustic power LpA < 55 dB (Cooling fan at high speed setting)
< 45 dB (Auto speed setting at 25 °C)

Fan speed settings of high, automatic, and off are available. The fan off setting can be enabled for a short period of time, except at higher ambient temperatures where the fan will stay on.

Abbreviations

dBVrms dB relative to 1 Volt rms.
dBfs dB relative to full scale amplitude range. Full scale is approx. 2 dB below ADC overload.
Typical Typical, non-warranted, performance specification included to provide general product information.

Environmental operating restrictions

	Operating: Disk in drive	Operating: No disk in drive	Storage & transport
Ambient temp.	4 °C to 45 °C	0 °C to 55 °C	-40 °C to 70 °C
Relative humidity (non-condensing)			
Minimum	20%	15%	5%
Maximum	80% at 32 °C	95% at 40 °C	95% at 50 °C
Vibrations (5 - 500 Hz)	0.6 Grms	1.5 Grms	3.41 Grms
Shock	5 G (10 mSec ½ sine)	5 G (10 mSec ½ sine)	40 G (3 mSec ½ sine)
Max. altitude	4600 meters (15,000 ft.)	4600 meters (15,000 ft.)	4600 meters (15,000 ft.)

AC power 90 Vrms - 264 Vrms (47 - 440 Hz)
350 VA maximum

DC power 12 VDC to 28 VDC nominal
200 VA maximum

DC current at 12 V Standard: <10 A typical
4 channel: <12 A typical

Warm-up time 15 minutes

Weight 15 kg (33 lb) net
29 kg (64 lb) shipping

Dimensions (Excluding bail handle and impact cover)

Height 190 mm (7.5")
Width 340 mm (13.4")
Depth 465 mm (18.3")

Remove all doubt

Our repair and calibration services will get your equipment back to you, performing like new, when promised. You will get full value out of your Agilent equipment through-out its lifetime. Your equipment will be serviced by Agilent-trained technicians using the latest factory calibration procedures, automated repair diagnostics and genuine parts. You will always have the utmost confidence in your measurements. For information regarding self maintenance of this product, please contact your Agilent office.

Agilent offers a wide range of additional expert test and measurement services for your equipment, including initial start-up assistance, onsite education and training, as well as design, system integration, and project management.

For more information on repair and calibration services, go to:

www.agilent.com/find/removealldoubt



Agilent Email Updates

www.agilent.com/find/emailupdates

Get the latest information on the products and applications you select.



Agilent Direct

www.agilent.com/find/agilentdirect

Quickly choose and use your test equipment solutions with confidence.

MS-DOS is a U.S. registered trademark of Microsoft Corporation.

MATLAB is a U.S. registered trademark of The Math Works, Inc.

For more information on Agilent Technologies' products, applications or services, please contact your local Agilent office. The complete list is available at:

www.agilent.com/find/contactus

Americas

Canada	(877) 894-4414
Latin America	305 269 7500
United States	(800) 829-4444

Asia Pacific

Australia	1 800 629 485
China	800 810 0189
Hong Kong	800 938 693
India	1 800 112 929
Japan	0120 (421) 345
Korea	080 769 0800
Malaysia	1 800 888 848
Singapore	1 800 375 8100
Taiwan	0800 047 866
Thailand	1 800 226 008

Europe & Middle East

Austria	01 36027 71571
Belgium	32 (0) 2 404 93 40
Denmark	45 70 13 15 15
Finland	358 (0) 10 855 2100
France	0825 010 700*
	*0.125 €/minute
Germany	07031 464 6333
Ireland	1890 924 204
Israel	972-3-9288-504/544
Italy	39 02 92 60 8484
Netherlands	31 (0) 20 547 2111
Spain	34 (91) 631 3300
Sweden	0200-88 22 55
Switzerland	0800 80 53 53
United Kingdom	44 (0) 118 9276201

Other European Countries:

www.agilent.com/find/contactus

Revised: October 1, 2008

Product specifications and descriptions in this document subject to change without notice.

© Agilent Technologies, Inc. 2009
Printed in USA, January 9, 2009
5966-3064E



Agilent Technologies