



Agilent E5250A

Low Leakage Switch Mainframe

Technical Data



Introduction

Basic Functions

Agilent E5250A Low Leakage Switch Mainframe functions:

- Switches DC current, DC voltage, capacitance and pulse with DC instruments and LCR meters
- Controls switching through built-in GPIB
- Performs self test using Option 301 relay function test adapter

Configurations

Option 001 10 x 12 matrix switch:
From 10 x 12 to 10 x 48 matrix per frame. (Option 001 x 1 to 4)

Option 501 24-channel (8 x 3) multiplexer:

From 24 to 96 channels per frame (Option 501 x 1 to 4)

Required cables and connector plates are available.

Furnished Program Disk

The E5250A includes a program disk (3.5-inch LIF format) that contains two utility and three sample programs.

Utility programs:

Virtual front panel, self test (IBASIC)

Sample programs and routines:

C compensation using Agilent 4284A application samples for this matrix switch and multiplexer. (HP BASIC) VFP setup data upload (HP BASIC)

Specification Condition

The Supplemental Information and Typical Data entries in the following specifications are not warranted but they provide useful information about the functions and performance of the instruments. Specifications, typical data, and supplemental information are defined at $23^{\circ}\text{C} \pm 5^{\circ}$ < 60% relative humidity (RH).



Agilent Technologies

Innovating the HP Way

General Specifications

Temperature Range	
Operating:	5° C to 40° C
Storage:	-40° C to 70° C
Humidity Range	
Operating:	5% to 80% (no condensation)
Storage:	5% to 90% RH at 65° C
Altitude	
Operating:	0 to 2000 m (6500 ft)
Storage:	0 to 15,240 m (50,000 ft)
Regulatory Compliance	
Safety:	CSA C22.2 No. 1010.1/IEC 1010-1
EMC:	CISPR 11 Group 1 class A&EN50082-1
Power Requirements:	100/120/220/240 V ± 10%, 47 Hz to 63 Hz
Maximum VA:	100 VA
No. of Slots:	4 slots for 30-mm height switch cards
Size	
Mainframe:	230 mm H x 430 mm W x 600 mm D
Option 001:	30 mm H x 395 mm W x 424 mm D
Option 501:	30 mm H x 395 mm W x 424 mm D
Weight (approx.)	
Mainframe:	11.2 kg
Option 001:	2.0 kg
Option 501:	2.1 kg
No. of Ports (with option 001)	
Low Leakage I-V Port:	2
General I-V Port:	4
C-V Port:	2
HF Port:	2
Output Channels:	12
No. of Ports (with option 501)	
Low Leakage I-V port:	3
Bias Port:	3
Output Channels:	24 (8 x 3)

Option 001 10 x 12 Matrix Switch

Switch Specification*

Condition	A	B	C
Max. Current rating (A):	1.0	-	-
Max. Voltage rating (V)			
Channel to Ground:	200	-	-
Channel to Channel:	300	-	-
Close Ch Residual R (Ω)			
Low Leakage I-V Port:	0.6	-	-
General I-V Port:	1.0	-	-
C-V, HF Port:	1.0	-	-
Ch Isolation R (Ω)			
Low Leakage I-V Port:	10^{13}	5×10^{12}	2×10^{12}
General I-V Port:	10^{12}	5×10^{11}	2×10^{11}
C-V, HF Port:	10^9	5×10^8	2×10^8
Condition A:	23° C ± 5° C, 5% to 60% RH		
Condition B:	5° C to 18° C, 28° C to 40° C, 5% to 60% RH		
Condition C:	28° C to 40° C, 60% to 80% RH		

*This specification is defined with the module plugged into the mainframe.

Typical Data

Offset current:	< 0.1 pA ¹	(Low Leakage I-V Port)
	< 1000 pA ¹	(General I-V Port)
Channel Crosstalk Capacitance:	< 0.3 pF/ch	
Offset voltage, Electro Motive Force (EMF) at 5 min.:	< 80 μV	(Low Leakage I-V Port)
	< 110 μV	(General I-V Port)
	< 110 μV	(C-V, HF Port)
Guard Capacitance:	< 145 pF ²	(Low Leakage I-V Port)
	< 123 pF ²	(General I-V Port)
Additional C measurement Error	< ±1% ±0.5 pF ³	(C-V Port)

Supplemental Information

Bandwidth (at -3 dB)	< 10 MHz	(C-V, HF Port)
Relay Contact Life:	> 10 ⁸ times	(Dry Switching Mode)
Settling Time:	< 3.5 sec to < 0.4 pA after 10 V applied	(Low Leakage I-V Port)

E5250A Option 501 24-Channel (8x3) Multiplexer

Switch Specification *

Condition	A	B	C
Max. Current rating (A):	1.0	-	-
Max. Voltage rating (V)			
Channel to Ground:	200	-	-
Channel to Channel:	300	-	-
Close Ch Residual R (Ω)			
Low Leakage I-V Port:	0.6	-	-
Bias Port:	1.0	-	-
Ch Isolation R (Ω)			
Low Leakage I-V Port:	10 ¹³	5 x 10 ¹²	2 x 10 ¹²
Bias Port:	10 ⁹	5 x 10 ⁸	2 x 10 ⁸
Condition A:	23° C ± 5° C, 5% to 60% RH		
Condition B:	5° C to 18° C, 28° C to 40° C, 5% to 60% RH		
Condition C:	28° C to 40° C, 60% to 80% RH		

*This specification is defined with the module plugged into the mainframe.

Typical Data

Offset current:	< 0.1 pA ⁴	(Low Leakage I-V Port)
Channel Crosstalk Capacitance:	< 0.4 pF/ch	(Low Leakage I-V Port)
	< 5 pF/ch	(Bias Port)
Offset voltage (EMF) at 5 min.:	< 80 μV	(Low Leakage I-V Port)
Guard Capacitance:	< 180 pF ⁵	(Low Leakage I-V Port)
	< 60 pF	(Low Leakage I-V Port, when the port is open)

Supplemental Information

Relay Contact Life:	> 10 ⁸ times	(Dry Switching Mode)
Settling Time	< 3.5 sec to < 0.4 pA after 10 V applied	(Low Leakage I-V Port)

¹The offset current when zero volts are applied to all input and output channels

²The guard capacitance of the closed port on input and output ports when one module per frame is installed

³The additional error using the C-Compensation program at 1 kHz ~ 1 MHz, < 1000 pF

⁴When zero volts are applied to all input and output channels

⁵The guard capacitance of the closed port on input and output ports when one module per frame is installed

Accessory Specifications

16494A	Triaxial Cable
16494B	Kelvin Triaxial Cable
16494C	Kelvin Triaxial Cable for 4142
16494D	8 ch Shielded Coaxial Cable
16495A	Connector Plate w/12 Triax. Intlk/GNDU
16495B	Connector Plate w/24 Triax. Intlk/GNDU
16495C	Connector Plate w/6 8 ch SHLD conn
16495D	Connector Plate w/12 8 ch SHLD conn
16495E	Half Size Blank Plate

General Specifications

Temperature Range

Operating:	5° C to 40° C
Storage:	-40° C to 70° C

Humidity Range

Operating:	5% to 80% (no condensation)
Storage:	5% to 90% RH at 65° C

16494E Wide Temperature 8 ch shielded Coaxial Cable

General Specifications

Temperature Range

Operating:	5° C to 40° C
	-50° C to 200° C (for cable only)
Storage:	-40° C to 70° C

Humidity Range

Operating:	5% to 80% (no condensation)
Storage:	5% to 90% RH at 65° C

4155C and 4156C Supplemental Information

4155C Supplemental Information

Data shows the degradation when using the 4155C with Low Leakage I-V Port.

Voltage Range and Offset Accuracy (with MPSMU)

Range	Setting	Measurement
2 V	960 μ V + (0.5 x Iout) V	780 μ V + (0.5 x Iout) V

Current Range and Offset Accuracy (with MPSMU)

Range	Setting	Measurement
1 nA	3 pA + (0.2 x Vout) pA	3 pA + (0.2 x Vout) pA
10 nA	7 pA + (0.2 x Vout) pA	5 pA + (0.2 x Vout) pA
100 nA	50 pA + (0.4 x Vout) pA	30 pA + (0.4 x Vout) pA

4156C Supplemental Information

Data shows the degradation when using the 4156C with Low Leakage I-V Port with non-kelvin connection.

Voltage Range and Offset Accuracy (with HRSMU)

Range	Setting	Measurement
2 V	500 μ V + (0.5 x Iout) V	280 μ V + (0.5 x Iout) V

Current Range and Offset Accuracy (with HRSMU)

Range	Setting	Measurement
10 pA	0.4 pA + (0.2 x Vout) pA	0.1 pA + (0.2 x Vout) pA
100 pA	0.4 pA + (0.2 x Vout) pA	0.1 pA + (0.2 x Vout) pA
1 nA	0.7 pA + (0.2 x Vout) pA	0.5 pA + (0.2 x Vout) pA
10 nA	4 pA + (0.2 x Vout) pA	2 pA + (0.2 x Vout) pA
100 nA	40 pA + (0.3 x Vout) pA	20 pA + (0.3 x Vout) pA

For more information about Agilent Technologies semiconductor test products, applications and services, visit our Website:

www.agilent.com/go/semiconductor or you can call one of the centers listed below and ask to speak with a semiconductor test sales representative.

For information about other Agilent test and measurement products, go to www.agilent.com.

United States:

Agilent Technologies
1 800 452 4844

Canada:

Agilent Technologies Canada Inc.
1 877 894 4414

Europe:

Agilent Technologies
(31 20) 547 2000

Japan:

Agilent Technologies Japan Ltd.
(81) 426 56 7832
Fax: (81) 426 56 7840

Latin America:

Agilent Technologies
(305) 269 7500
Fax: (305) 269 7599

Australia/New Zealand:

Agilent Technologies Australia Pty Ltd
1-800 629 485 (Australia)
Fax: (61 3) 9272 0749
0 800 738 378 (New Zealand)
Fax: (64 4) 495 8950

Asia Pacific:

Agilent Technologies
(852) 2599 7889
Fax: (852) 2506 9233

Taiwan:

Agilent Technologies
(886-2) 717-9524
Fax: (886) 2 718 9860

Korea:

(822)769-0800
Fax:(822) 786-1083

Singapore:

(65)1800-292 8100
Fax:(65) 275 0387

©Copyright 2000 Agilent Technologies.
Technical data subject to change without notice.
Printed in the USA December 1, 2000
5964-2378E