


Agilent MXA Signal Analyzer N9020A

Data Sheet

Available frequency ranges

| | |
|------------|-------------------|
| N9020A-503 | 20 Hz to 3.6 GHz |
| N9020A-508 | 20 Hz to 8.4 GHz |
| N9020A-513 | 20 Hz to 13.6 GHz |
| N9020A-526 | 20 Hz to 26.5 GHz |



LXI class C certified



Agilent Technologies

Table of Contents

| | |
|--|-----------|
| Definitions and Conditions | 3 |
| Frequency and Time Specifications | 4 |
| Frequency range | 4 |
| Band | 4 |
| Frequency reference | 4 |
| Frequency readout accuracy | 4 |
| Marker frequency counter | 4 |
| Frequency span | 5 |
| Sweep time and triggering | 5 |
| Time gating | 5 |
| Sweep (trace) point range | 5 |
| Resolution bandwidth (RBW) | 5 |
| Analysis bandwidth | 6 |
| Video bandwidth (VBW) | 6 |
| Measurement speed | 6 |
| Amplitude Accuracy and Range Specifications | 7 |
| Amplitude range | 7 |
| Electronic attenuator | 7 |
| Maximum safe input level | 7 |
| Display range | 7 |
| Frequency response | 8 |
| Input attenuation switching uncertainty | 8 |
| Total absolute amplitude accuracy | 8 |
| Input voltage standing wave ratio (VSWR) | 8 |
| Resolution bandwidth switching uncertainty | 9 |
| Reference level | 9 |
| Display scale switching uncertainty | 9 |
| Display scale fidelity | 9 |
| Trace detectors | 9 |
| Preamplifier | 9 |
| Dynamic Range Specifications | 10 |
| 1 dB gain compression (two tone) | 10 |
| Displayed average noise level (DANL) | 10 |
| Spurious responses | 10 |
| Second harmonic distortion (SHD) | 11 |
| Third-order intermodulation distortion (TOI) | 11 |
| Phase noise | 12 |

Power Suite Measurement Specifications

| | |
|---|-----------|
| Power Suite Measurement Specifications | 13 |
| Channel power | 13 |
| Occupied bandwidth | 13 |
| Adjacent channel power | 13 |
| Power statistics CCDF | 13 |
| Burst power | 14 |
| Spurious emission | 14 |
| Spectrum emission mask (SEM) | 14 |
| General Specifications | 15 |
| Temperature range | 15 |
| EMC | 15 |
| Safety | 15 |
| Audio noise | 15 |
| Environmental stress | 15 |
| Power requirements | 16 |
| Data storage | 16 |
| Weight | 16 |
| Dimensions | 16 |
| Warranty | 16 |
| Calibration cycle | 16 |
| Inputs and Outputs | 17 |
| Front panel | 17 |
| Rear panel | 17 |
| MXA Signal Analyzer Ordering Information | 19 |
| Hardware | 19 |
| Applications | 19 |
| Accessories | 20 |
| Warranty and service | 20 |
| Calibration | 20 |
| Related Literature | 21 |
| Support, Services, and Assistance | 22 |

The MXA signal analyzer takes signal and spectrum analysis to the next generation, offering the highest performance in a midrange signal analyzer with the industry's fastest signal and spectrum analysis, eliminating the compromise between speed and performance. With a broad set of applications and demodulation capabilities, an intuitive user interface, outstanding connectivity and powerful one-button measurements, the MXA is ideal for both R&D and manufacturing engineers working on cellular, emerging wireless communications, general purpose, aerospace and defense applications.

Definitions and Conditions

Specifications describe the performance of parameters covered by the product warranty and apply over 5 to 50 °C unless otherwise noted. 95th percentile values indicate the breadth of the population ($\approx 2\sigma$) of performance tolerances expected to be met in 95 percent of the cases with a 95 percent confidence, for any ambient temperature in the range of 20 to 30 °C. In addition to the statistical observations of a sample of instruments, these values include the effects of the uncertainties of external calibration references. These values are not warranted. These values are updated occasionally if a significant change in the statistically observed behavior of production instruments is observed. Typical describes additional product performance information that is not covered by the product warranty. It is performance beyond specifications that 80 percent of the units exhibit with a 95 percent confidence level over the temperature range 20 to 30-°C. Typical performance does not include measurement uncertainty. Nominal values indicate expected performance, or describe product performance that is useful in the application of the product, but is not covered by the

product warranty. The analyzer will meet its specifications when:

- The analyzer is within its calibration cycle.
- Under auto couple control, except that Auto Sweep Time Rules = Accy.
- For signal frequencies <20-MHz, DC coupling applied.
- The analyzer has been stored at an ambient temperature within the allowed operating range for at least two hours before being turned on, if it had previously been stored at a temperature range inside the allowed storage range but outside the allowed operating range.
- The analyzer has been turned on at least 30 minutes with Auto Align set to normal, or if Auto Align is set to off or partial, alignments must have been run recently enough to prevent an Alert message. If the Alert condition is changed from Time and Temperature to one of the disabled duration choices, the analyzer may fail to meet specifications without informing the user.

This MXA signal analyzer data sheet is a summary of the complete specifications and conditions, which are available in the *MXA Signal Analyzer Specification Guide*. The *MXA Signal Analyzer Specification Guide* can be obtained on the web at: www.agilent.com/find/mxa_manuals.

Frequency and Time Specifications

| Frequency range | DC Coupled | AC Coupled |
|-----------------|-------------------|--------------------|
| Option 503 | 20 Hz to 3.6 GHz | 10 MHz to 3.6 GHz |
| Option 508 | 20 Hz to 8.4 GHz | 10 MHz to 8.4 GHz |
| Option 513 | 20 Hz to 13.6 GHz | 10 MHz to 13.6 GHz |
| Option 526 | 20 Hz to 26.5 GHz | 10 MHz to 26.5 GHz |

| Band | LO Multiple (N) | |
|------|-----------------|------------------|
| 0 | 1 | 20 Hz to 3.6 GHz |
| 1 | 1 | 3.5 to 8.4 GHz |
| 2 | 2 | 8.3 to 13.6 GHz |
| 3 | 2 | 13.5 to 17.1 GHz |
| 4 | 4 | 17 to 26.5 GHz |

Frequency reference

| | | |
|---|--|--|
| Accuracy | \pm [(time since last adjustment x aging rate) + temperature stability + calibration accuracy] | |
| Aging rate | Option PFR $\pm 1 \times 10^{-7}$ / year $\pm 1.5 \times 10^{-7}$ / 2 years | Standard $\pm 1 \times 10^{-6}$ / year |
| Temperature stability 20 to 30 °C 5 to 50 °C | Option PFR $\pm 1.5 \times 10^{-8}$ $\pm 5 \times 10^{-8}$ | Standard $\pm 2 \times 10^{-6}$ $\pm 2 \times 10^{-6}$ |
| Achievable initial calibration accuracy | Option PFR $\pm 4 \times 10^{-8}$ | Standard $\pm 1.4 \times 10^{-6}$ |
| Example frequency reference accuracy (with Option PFR) 1 year after last adjustment | $= \pm(1 \times 10^{-7} + 5 \times 10^{-8} + 4 \times 10^{-8})$ $= \pm 1.9 \times 10^{-7}$ | |
| Residual FM Option PFR Standard | $\leq (0.25 \text{ Hz} \times N)$ p-p in 20 ms nominal $\leq (10 \text{ Hz} \times N)$ p-p in 20 ms nominal See band table above for N (LO Multiple) | |

Frequency readout accuracy (*start, stop, center, marker*)

$$\pm (\text{marker frequency} \times \text{frequency reference accuracy} + 0.25\% \times \text{span} + 5\% \times \text{RBW} + 2 \text{ Hz} + 0.5 \times \text{horizontal resolution}^1)$$

¹ Horizontal resolution is span/(sweep points - 1)

Marker frequency counter

| | |
|------------------------|--|
| Accuracy | \pm (marker frequency x frequency reference accuracy + 0.100 Hz) |
| Delta counter accuracy | \pm (delta frequency x frequency reference accuracy + 0.141 Hz) |
| Counter resolution | 0.001 Hz |

Frequency and Time Specifications (continued)

Frequency span (FFT and swept mode)

| | | |
|------------|---|--|
| Range | 0 Hz (zero span), 10 Hz to maximum frequency of instrument | |
| Resolution | 2 Hz | |
| Accuracy | | |
| Swept | $\pm(0.25\% \times \text{span} + \text{horizontal resolution})$ | |
| FFT | $\pm(0.10\% \times \text{span} + \text{horizontal resolution})$ | |

Sweep time and triggering

| | | |
|---------------|---|--|
| Range | Span = 0 Hz Span \geq 10 Hz | 1 μ s to 6000 s 1 ms to 4000 s |
| Accuracy | Span \geq 10 Hz, swept Span \geq 10 Hz, FFT Span = 0 Hz | $\pm 0.01\%$ nominal $\pm 40\%$ nominal $\pm 0.01\%$ nominal |
| Trigger | Free run, line, video, external 1, external 2, RF burst, periodic timer | |
| Trigger delay | Span = 0 Hz or FFT Span \geq 10 Hz, swept Resolution | -150 to +500 ms 1 μ s to 500 ms 0.1 μ s |

Time gating

| | |
|--|----------------------------------|
| Gate methods: | Gated LO; Gated video; Gated FFT |
| Gate length range (except method = FFT): | 100.0 ns to 5.0 s |
| Gate delay range: | 0 to 100.0 s |
| Gate delay jitter: | 33.3 ns p-p nominal |

Sweep (trace) point range

| | |
|-----------|------------|
| All spans | 1 to 20001 |
|-----------|------------|

Resolution bandwidth (RBW)

| | | |
|-------------------------------|---|-------------------------------|
| Range (-3.01 dB bandwidth) | 1 Hz to 3 MHz (10% steps), 4, 5, 6, 8 MHz | |
| Bandwidth accuracy (power) | 1 Hz to 750 kHz | $\pm 1.0\%$ (± 0.044 dB) |
| RBW range | 820 kHz to 1.2 MHz (< 3.6 GHz CF) | $\pm 2.0\%$ (± 0.088 dB) |
| | 1.3 to 2.0 MHz (<3.6 GHz CF) | ± 0.07 dB nominal |
| | 2.2 to 3 MHz (<3.6 GHz CF) | ± 0.15 dB nominal |
| | 4 to 8 MHz (<3.6 GHz CF) | ± 0.25 dB nominal |
| Bandwidth accuracy (-3.01 dB) | 1 Hz to 1.3 MHz | $\pm 2\%$ nominal |
| RBW range | | |
| Selectivity (-60 dB/-3 dB) | 4.1:1 nominal | |

Frequency and Time Specifications (continued)

Analysis bandwidth²

| | |
|-------------------|--------|
| Maximum bandwidth | |
| Option B25 | 25 MHz |
| Standard | 10 MHz |

² Analysis bandwidth is the instantaneous bandwidth available around a center frequency over which the input signal can be digitized for further analysis or processing in the time, frequency, or modulation domain.

Video bandwidth (VBW)

| | |
|----------|--|
| Range | 1 Hz to 3 MHz (10% steps), 4, 5, 6, 8 MHz and wide open (labeled 50 MHz) |
| Accuracy | ±6% nominal |

Measurement speed

| | | |
|---|---------------------|-----------------------|
| Local measurement and display update rate | Sweep points = 1001 | 11 ms (90/s) nominal |
| Remote measurement and LAN transfer rate | Sweep points = 1001 | 4 ms (250/s) nominal |
| Marker peak search | 5 ms nominal | |
| Center frequency tune and transfer (RF) | 51 ms nominal | |
| Center frequency tune and transfer (μ W) | 86 ms nominal | |
| Measurement/mode switching | 75 ms nominal | |

Amplitude Accuracy and Range Specifications

Amplitude range

| | |
|---|--|
| Measurement range | Displayed average noise level (DANL) to maximum safe input level |
| Input attenuator range (20 Hz to 26.5 GHz) | 0 to 70 dB in 2 dB steps |

Electronic attenuator (Option EA3)

| | |
|---|------------------------|
| Frequency range | 20 Hz to 3.6 GHz |
| Attenuation range | |
| Electronic attenuator range | 0 to 24 dB, 1 dB steps |
| Full attenuation range (mechanical + electronic) | 0 to 94 dB, 1 dB steps |

Maximum safe input level

| | |
|------------------------------------|---|
| Average total power | +30 dBm (1 W) |
| Preamp (Option P03, P08, P13, P26) | +25 dBm |
| Peak pulse power | <10 μ s pulse width, <1% duty cycle +50 dBm (100 W) and input attenuation \geq 30 dB |
| DC volts | |
| DC coupled | \pm 0.2 Vdc |
| AC coupled | \pm 70 Vdc |

Display range

| | |
|--------------|---|
| Log scale | 0.1 to 1 dB/division in 0.1 dB steps 1 to 20 dB/division in 1 dB steps (10 display divisions) |
| Linear scale | 10 divisions |
| Scale units | dBm, dBmV, dB μ V, dBmA, dB μ A, V, W, A |

Amplitude Accuracy and Range Specifications (continued)

Frequency response (10 dB input attenuation, 20 to 30 °C, preselector centering applied, σ = nominal standard deviation)

| | | Specification | 95 th Percentile ($\approx 2\sigma$) |
|---|--------------------|---------------|---|
| | 20 Hz to 10 MHz | ± 0.6 dB | ± 0.28 dB |
| | 10 MHz to 3.6 GHz | ± 0.45 dB | ± 0.17 dB |
| | 3.5 to 8.4 GHz | ± 1.5 dB | ± 0.48 dB |
| | 8.3 to 13.6 GHz | ± 2.0 dB | ± 0.47 dB |
| | 13.5 to 22.0 GHz | ± 2.0 dB | ± 0.52 dB |
| | 22.0 to 26.5 GHz | ± 2.5 dB | ± 0.71 dB |
| Preamp on (Option P03, P08, P13, P26) attenuation 0 dB | 100 kHz to 3.6 GHz | ± 0.75 dB | ± 0.28 dB |
| | 3.5 to 8.4 GHz | ± 2.0 dB | ± 0.53 dB |
| | 8.3 to 13.6 GHz | ± 2.3 dB | ± 0.60 dB |
| | 13.5 to 17.1 GHz | ± 2.5 dB | ± 0.81 dB |
| | 17.0 to 22.0 GHz | ± 2.5 dB | ± 0.81 dB |
| | 22.0 to 26.5 GHz | ± 3.5 dB | ± 1.25 dB |

Input attenuation switching uncertainty

| | | | |
|--|--|---------------|-----------------------|
| | 50 MHz (reference frequency) attenuation > 2 dB | ± 0.20 dB | ± 0.08 dB typical |
| | 20 Hz to 3.6 GHz | | ± 0.3 dB nominal |
| | 3.5 to 8.4 GHz | | ± 0.5 dB nominal |
| | 8.3 to 13.6 GHz | | ± 0.7 dB nominal |
| | 13.5 to 26.5 GHz | | ± 0.7 dB nominal |

Total absolute amplitude accuracy (10 dB attenuation, 20 to 30 °C, $1 \text{ Hz} \leq \text{RBW} \leq 1 \text{ MHz}$, input signal -10 to -50 dBm, all settings auto-coupled except Auto Swp Time = Accy, any reference level, any scale, σ = nominal standard deviation)

| | | | |
|---------------------------------------|--------------------|--|--|
| | At 50 MHz | ± 0.33 dB | |
| | At all frequencies | $\pm (0.33 \text{ dB} + \text{frequency response})$ | |
| | 20 Hz to 3.6 GHz | ± 0.23 dB (95 th Percentile $\approx 2\sigma$) | |
| Preamp on (Option P03, P08, P13, P26) | At all frequencies | $\pm (0.39 \text{ dB} + \text{frequency response})$ | |

Input voltage standing wave ratio (VSWR) (≥ 10 dB input attenuation)

| | | |
|---|-------------------|-----------------|
| | 10 MHz to 3.6 GHz | < 1.2:1 nominal |
| | 3.6 to 8.4 GHz | < 1.5:1 nominal |
| | 8.4 to 13.6 GHz | < 1.6:1 nominal |
| | 13.6 to 26.5 GHz | < 1.9:1 nominal |
| Preamp on (Option P03, P08, P13, P26) (0 dB attenuation) | 10 MHz to 3.6 GHz | < 1.7:1 nominal |
| | 3.6 to 8.4 GHz | < 1.8:1 nominal |
| | 8.4 to 13.6 GHz | < 2.0:1 nominal |
| | 13.6 to 26.5 GHz | < 2.0:1 nominal |

Amplitude Accuracy and Range Specifications (continued)

Resolution bandwidth switching uncertainty (referenced to 30 kHz RBW)

| | |
|----------------------|----------|
| 1 Hz to 1.5 MHz RBW | ±0.05 dB |
| 1.6 MHz to 3 MHz RBW | ±0.10 dB |
| 4, 5, 6, 8 MHz RBW | ±1.0 dB |

Reference level

| | |
|--------------|----------------------------------|
| Range | |
| Log scale | -170 to +30 dBm in 0.01 dB steps |
| Linear scale | Same as Log (707 pV to 7.07 V) |
| Accuracy | 0 dB |

Display scale switching uncertainty

| | |
|----------------------------------|------|
| Switching between linear and log | 0 dB |
| Log scale/div switching | 0 dB |

Display scale fidelity

| | |
|---|----------------|
| Between -10 dBm and -80 dBm input mixer level | ±0.10 dB total |
|---|----------------|

Trace detectors

Normal, peak, sample, negative peak, log power average, RMS average, and voltage average

Preamplifier

| | | |
|-----------------|--------------------|---------------------|
| Frequency range | Option P03 | 100 kHz to 3.6 GHz |
| | Option P08 | 100 kHz to 8.4 GHz |
| | Option P13 | 100 kHz to 13.6 GHz |
| | Option P26 | 100 kHz to 26.5 GHz |
| Gain | 100 kHz to 3.6 GHz | +20 dB nominal |
| | 3.6 to 26.5 GHz | +35 dB nominal |
| Noise figure | 100 kHz to 3.6 GHz | 11 dB nominal |
| | 3.6 to 8.4 GHz | 9 dB nominal |
| | 8.4 to 13.6 GHz | 10 dB nominal |
| | 13.6 to 26.5 GHz | 15 dB nominal |

Dynamic Range Specifications

1 dB gain compression (two-tone)

| | | Total power at input mixer | |
|---------------------------------------|--------------------------------|----------------------------|-----------------|
| | 20 to 500 MHz | 0 dBm | +3 dBm typical |
| | 500 MHz to 3.6 GHz | +3 dBm | +7 dBm typical |
| | 3.6 to 26.5 GHz | 0 dBm | +4 dBm typical |
| Preamp on (Option P03, P08, P13, P26) | 10 MHz to 3.6 GHz | | -10 dBm nominal |
| | 3.6 to 26.5 GHz | | |
| | Tone spacing 100 kHz to 20 MHz | | -26 dBm nominal |
| | Tone spacing >70 MHz | | -16 dBm nominal |

Displayed average noise level (DANL)

(Input terminated, sample or average detector, averaging type = Log, 0 dB input attenuation, IF Gain = High, 20 to 30 °C)

| | | Specification | Typical |
|---------------------------------------|-------------------|---------------|----------|
| Preamp off | 9 kHz to 1 MHz | | -125 dBm |
| | 1 to 10 MHz | -150 dBm | -153 dBm |
| | 10 MHz to 2.1 GHz | -151 dBm | -154 dBm |
| | 2.1 to 3.6 GHz | -149 dBm | -152 dBm |
| | 3.6 to 8.4 GHz | -149 dBm | -153 dBm |
| | 8.4 to 13.6 GHz | -148 dBm | -151 dBm |
| | 13.6 to 17.1 GHz | -144 dBm | -147 dBm |
| | 17.1 to 20.0 GHz | -143 dBm | -146 dBm |
| Preamp on (Option P03, P08, P13, P26) | 20.0 to 26.5 GHz | -136 dBm | -142 dBm |
| | 100 kHz to 1 MHz | | -149 dBm |
| | 1 to 10 MHz | -161 dBm | -163 dBm |
| | 10 MHz to 2.1 GHz | -163 dBm | -166 dBm |
| | 2.1 to 3.6 GHz | -162 dBm | -164 dBm |
| | 3.6 to 8.4 GHz | -162 dBm | -166 dBm |
| | 8.4 to 13.6 GHz | -162 dBm | -165 dBm |
| | 13.6 to 17.1 GHz | -159 dBm | -163 dBm |
| 17.1 to 20.0 GHz | -157 dBm | -161 dBm | |
| 20.0 to 26.5 GHz | -152 dBm | -157 dBm | |

Spurious responses

| | | |
|--|---------------------------------------|----------------------------|
| Residual responses (Input terminated and 0 dB attenuation) | 200 kHz to 8.4 GHz (swept) | -100 dBm |
| | Zero span or FFT or other frequencies | -100 dBm nominal |
| Image responses | 10 MHz to 3.6 GHz | -80 dBc (-107 dBc typical) |
| | 3.6 to 13.6 GHz | -78 dBc (-88 dBc typical) |
| | 13.6 to 17.1 GHz | -74 dBc (-85 dBc typical) |
| | 17.1 to 22 GHz | -70 dBc (-82 dBc typical) |
| | 22 to 26.5 GHz | -68 dBc (-78 dBc typical) |
| LO related spurious (f > 600 MHz from carrier) | 10 MHz to 3.6 GHz | -90 dBc typical |
| Other spurious (f ≥ 10 MHz from carrier) | | -80 dBc |

Dynamic Range Specifications (continued)

Second harmonic distortion (SHI)

| | Mixer level | Distortion | SHI |
|---------------------------------------|--------------|-----------------|-----------------|
| 10 MHz to 1.8 GHz | -15 dBm | -60 dBc | +45 dBm |
| 1.8 to 7.0 GHz | -15 dBm | -80 dBc | +65 dBm |
| 7.0 to 11.0 GHz | -15 dBm | -70 dBc | +55 dBm |
| 11.0 to 13.25 GHz | -15 dBm | -65 dBc | +50 dBm |
| <hr/> | | | |
| Preamp on (Option P03, P08, P13, P26) | Preamp level | Distortion | SHI |
| 10 MHz to 1.8 GHz | -45 dBm | -78 dBc nominal | +33 dBm nominal |
| 1.8 to 13.25 GHz | -50 dBm | -60 dBc nominal | +10 dBm nominal |

Third-order intermodulation distortion (TOI) (two -30 dBm tones at input mixer with tone separation > 5 times IF prefilter bandwidth, 20 to 30 degC, see Specifications Guide for IF prefilter bandwidths)

| | Distortion | TOI | Typical |
|---------------------------------------|--------------------|-----------------|---------|
| 10 to 100 MHz | -84 dBc | +12 dBm | +17 dBm |
| 100 to 400 MHz | -88 dBc | +14 dBm | +18 dBm |
| 400 MHz to 1.7 GHz | -90 dBc | +15 dBm | +19 dBm |
| 1.7 to 3.6 GHz | -92 dBc | +16 dBm | +19 dBm |
| 3.6 to 8.4 GHz | -90 dBc | +15 dBm | +18 dBm |
| 8.4 to 13.6 GHz | -90 dBc | +15 dBm | +18 dBm |
| 13.6 to 26.5 GHz | -80 dBc | +10 dBm | +14 dBm |
| <hr/> | | | |
| Preamp on (Option P03, P08, P13, P26) | 10 to 500 MHz | +4 dBm nominal | |
| (two -45 dBm tones at preamp input) | 500 MHz to 3.6 GHz | +5 dBm nominal | |
| | 3.6 to 26.5 GHz | -15 dBm nominal | |




Figure 1. Nominal dynamic range – Band 0, for second and third order distortion, 20 Hz to 3.6 GHz




Figure 2. Nominal dynamic range – Bands 1 to 4, second and third order distortion, 3.6 GHz to 26.5 GHz

Dynamic Range Specifications (continued)

Phase noise³

| Noise sidebands (20 to 30 °C, CF = 1 GHz) | Offset | Specification | Typical |
|--|---------|---------------|---------------------|
| | 100 Hz | -84 dBc/Hz | -88 dBc/Hz |
| | 1 kHz | | -100 dBc/Hz nominal |
| | 10 kHz | -103 dBc/Hz | -106 dBc/Hz |
| | 100 kHz | -115 dBc/Hz | -117 dBc/Hz |
| | 1 MHz | -133 dBc/Hz | -137 dBc/Hz |
| | 10 MHz | | -148 dBc/Hz nominal |

3 For nominal values, refer to Figure 3.




Figure 3. Nominal phase noise at different center frequencies (with Option PFR)

Power Suite Measurement Specifications

Channel power

| | |
|---|-------------------------------------|
| Amplitude accuracy, W-CDMA or IS95 (20 to 30 °C, attenuation = 10 dB) | ±0.80 dB (±0.30 dB 95th percentile) |
|---|-------------------------------------|

Occupied bandwidth

| | |
|--------------------|-----------------------|
| Frequency accuracy | ± [span/1000] nominal |
|--------------------|-----------------------|

Adjacent channel power

Accuracy, W-CDMA (ACLR) (at specific mixer levels and ACLR ranges)

| | Adjacent | Alternate |
|-----|----------|-----------|
| MS | ±0.14 dB | ±0.21 dB |
| BTS | ±0.49 dB | ±0.44 dB |

Dynamic range (typical)

| | | |
|--------------------------|--------|--------|
| Without noise correction | -73 dB | -79 dB |
| With noise correction | -78 dB | -82 dB |

Offset channel pairs measured

1 to 6

ACP speed (fast method). Data measurement and transfer time

14 ms nominal ($\sigma = 0.2$ dB)

ACPR dynamic range, W-CDMA (5 MHz offset, RRC weighted, 3.84 MHz noise bandwidth)

| | |
|-----------------------|----------------|
| Two carriers | -70 dB nominal |
| Four carriers | -64 dB nominal |
| With noise correction | -72 dB nominal |

ACPR accuracy (two carriers, 5 MHz offset, -48 dBc ACPR)

±0.42 dB nominal

Multiple number of carriers measured

Up to 12

Power statistics CCDF

| | |
|----------------------|---------|
| Histogram resolution | 0.01 dB |
|----------------------|---------|

Power Suite Measurement Specifications (continued)

Burst power

| | |
|---------|---|
| Methods | Power above threshold, power within burst width |
| Results | Single burst output power, average output power, maximum power, minimum power within burst, burst width |

Spurious emission

W-CDMA (1 to 3.6 GHz)

Table driven spurious signals; search across regions.

| | |
|----------------------|-------------------------------|
| Dynamic range | 95.3 dB (100.3 dB typical) |
| Absolute sensitivity | -84.4 dBm (-89.4 dBm typical) |

Spectrum emission mask (SEM)

cdma2000® (750 kHz offset)

| | |
|-------------------------------------|--------------------------------|
| Relative dynamic range (30 kHz RBW) | 78.9 dB (85.0 dB typical) |
| Absolute sensitivity | -99.7 dBm (-104.7 dBm typical) |
| Relative accuracy | ±0.11 dB |

3GPP W-CDMA (2.515 MHz offset)

| | |
|-------------------------------------|--------------------------------|
| Relative dynamic range (30 kHz RBW) | 81.9 dB (88.2 dB typical) |
| Absolute sensitivity | -99.7 dBm (-104.7 dBm typical) |
| Relative accuracy | ±0.12 dB |

General Specifications

Temperature range

| | |
|-----------|---------------|
| Operating | 5 to +50 °C |
| Storage | -40 to +65 °C |

EMC

Complies with European EMC Directive 89/336/EEC, amended by 93/68/EEC

- IEC/EN 61326
 - CISPR Pub 11 Group 1, class A
 - AS/NZS CISPR 11:2002
 - ICES/NMB-001
-

Safety

Complies with European Low Voltage Directive 73/23/EEC, amended by 93/68/EEC

- IEC/EN 61010-1
 - Canada: CSA C22.2 No. 61010-1
 - USA: UL 61010-1
-

Audio noise

| | |
|-------------------------|---------------------|
| Acoustic noise emission | Geraeuschemission |
| LpA <70 dB | LpA <70 dB |
| Operator position | Am Arbeitsplatz |
| Normal position | Normaler Betrieb |
| Per ISO 7779 | Nach DIN 45635 t.19 |

Environmental stress

Samples of this product have been type tested in accordance with the Agilent Environmental Test Manual and verified to be robust against the environmental stresses of storage, transportation and end-use; those stresses include but are not limited to temperature, humidity, shock, vibration, altitude and power line conditions. Test methods are aligned with IEC 60068-2 and levels are similar to MIL-PRF-28800F Class 3.

General Specifications (continued)

Power requirements

| | |
|---------------------------------|--|
| Voltage and frequency (nominal) | 100/120 V, 50/60 Hz 220/240 V, 50/60 Hz |
|---------------------------------|--|

Power consumption

| | |
|---------|-------------|
| On | < 260 watts |
| Standby | < 20 watts |

Data storage

| | |
|----------|---------------|
| Internal | 40 GB nominal |
|----------|---------------|

| | |
|----------|--|
| External | Supports USB 2.0 compatible memory devices |
|----------|--|

Weight (without options)

| | |
|----------|------------------------|
| Net | 16 kg (35 lbs) nominal |
| Shipping | 28 kg (62 lbs) nominal |

Dimensions

| | |
|--------|-----------------|
| Height | 177 mm (7.0 in) |
|--------|-----------------|

| | |
|-------|------------------|
| Width | 426 mm (16.8 in) |
|-------|------------------|

| | |
|--------|------------------|
| Length | 368 mm (14.5 in) |
|--------|------------------|

Warranty

The MXA signal analyzer is supplied with a one-year warranty.

Calibration cycle

The recommended calibration cycle is one year. Calibration services are available through Agilent service centers.

Inputs and Outputs

Front panel

| | |
|------------------|---|
| RF input | |
| Connector | Type-N female, 50 Ω nominal |
| Probe power | |
| Voltage/current | +15 Vdc, $\pm 7\%$ at 150 mA max nominal -12.6 Vdc, $\pm 10\%$ at 150 mA max nominal |
| USB 2.0 ports | |
| Master (2 ports) | |
| Standard | Compatible with USB 2.0 |
| Connector | USB Type-A female |
| Output current | 0.5 A nominal |

Rear panel

| | |
|---------------------------------|--|
| 10 MHz out | |
| Connector | BNC female, 50 Ω nominal |
| Output amplitude | ≥ 0 dBm nominal |
| Frequency | 10 MHz \pm (10 MHz x frequency reference accuracy) |
| Ext Ref In | |
| Connector | BNC female, 50 Ω nominal |
| Input amplitude range | -5 to +10 dBm nominal |
| Input frequency | 1 to 50 MHz nominal |
| Frequency lock range | $\pm 5 \times 10^{-6}$ of specified external reference input frequency |
| Trigger 1 and trigger 2 inputs | |
| Connector | BNC female |
| Impedance | >10 k Ω nominal |
| Trigger level range | -5 to +5 V |
| Trigger 1 and trigger 2 outputs | |
| Connector | BNC female |
| Impedance | 50 Ω nominal |
| Level | 5 V TTL nominal |

Inputs and Outputs (continued)

Rear panel (continued)

| | |
|--|--|
| Sync (reserved for future use) | |
| Connector | BNC female |
| Monitor output | |
| Connector | VGA compatible, 15-pin mini D-SUB |
| Format | XGA (60 Hz vertical sync rates, non-interlaced) Analog RGB |
| Resolution | 1024 x 768 |
| Noise source drive +28 V (pulsed) (reserved for future use) | |
| Connector | BNC female |
| SNS series noise source (reserved for future use) | |
| Digital bus (reserved for future use) | |
| Connector | MDR-80 |
| Analog out (reserved for future use) | |
| Connector | BNC female |
| USB 2.0 ports | |
| Master (4 ports) | |
| Standard | Compatible with USB 2.0 |
| Connector | USB Type-A female |
| Output current | 0.5 A nominal |
| Slave (1 port) | |
| Standard | Compatible with USB 2.0 |
| Connector | USB Type-B female |
| Output current | 0.5 A nominal |
| GPIB interface | |
| Connector | IEEE-488 bus connector |
| GPIB codes | SH1, AH1, T6, SR1, RL1, PP0, DC1, C1, C2, C3, C28, DT1, L4, C0 |
| LAN TCP/IP interface | |
| Standard | 100BaseT |
| Connector | RJ45 Ethertwist |

MXA Signal Analyzer Ordering Information

For further information, refer to MXA Signal Analyzer Configuration Guide (5989-4943EN)

Hardware

| | |
|------------|------------------------------------|
| N9020A | MXA signal analyzer |
| N9020A-503 | Frequency range, 20 Hz to 3.6 GHz |
| N9020A-508 | Frequency range, 20 Hz to 8.4 GHz |
| N9020A-513 | Frequency range, 20 Hz to 13.6 GHz |
| N9020A-526 | Frequency range, 20 Hz to 26.5 GHz |
| N9020A-B25 | Analysis bandwidth, 25 MHz |
| N9020A-PFR | Precision frequency reference |
| N9020A-EA3 | Electronic attenuator, 3.6 GHz |
| N9020A-P03 | Preamplifier, 3.6 GHz |
| N9020A-P08 | Preamplifier, 8.4 GHz |
| N9020A-P13 | Preamplifier, 13.6 GHz |
| N9020A-P26 | Preamplifier, 26.5 GHz |

Applications

| | |
|------------|--|
| N9063A | Analog demodulation measurement application (Orderable December 2007) |
| N9068A | Phase noise measurement application |
| N9071A | GSM/EDGE measurement application |
| N9073A-1FP | W-CDMA measurement application |
| N9073A-2FP | HSDPA/HSUPA measurement application (requires N9073A-1FP) |
| N9075A | 802.16 OFDMA measurement application |
| N9069A | Noise figure measurement application (Orderable December 2007) |
| N9072A | cdma2000 measurement application (Orderable December 2007) |
| N9079A-1FP | TD-SCDMA measurement application (Orderable December 2007) |
| N9079A-2FP | HSDPA/8PSK measurement application (requires N9079A-1FP) (Orderable December 2007) |
| 89601A | Vector signal analysis software |

MXA Signal Analyzer Ordering Information (continued)

For further information, refer to MXA Signal Analyzer Configuration Guide (5989-4943EN)

Accessories

| | |
|-------------|---|
| N9020A-CPU | Instrument security, additional CPU/HDD |
| N9020A-MSE | Mouse |
| N9020A-KYB | Keyboard |
| N9020A-EFM | USB flash drive, 1 GB |
| N9020A-DVR | USB DVD-ROM/CD-R/RW drive |
| N9020A-MLP | Minimum loss pad, 50 to 75 Ω |
| N9020A-PRC | Portable configuration |
| N9020AK-CVR | Front panel cover, additional |
| N9020A-1CP | Rack mount and handle kit |
| N9020A-1CM | Rack mount kit |
| N9020A-1CN | Front handle kit |
| N9020A-1CR | Rack slide kit |
| N9020A-HTC | Hard transit case |

Warranty and service

Standard warranty is one year.

| | |
|--------------|---|
| R-51B-001-3C | 1 year return-to-Agilent warranty extended to 3 years |
|--------------|---|

Calibration

| | |
|-------------|---|
| N9020A-1A7 | ISO 17025 compliant calibration |
| N9020A-A6J | ANSI Z540 compliant calibration |
| R-50C-011-3 | Inclusive calibration plan, 3 year coverage ⁴ |
| R-50C-013-3 | Inclusive calibration plan and cal data, 3 year coverage ⁴ |

⁴ Options not available in all countries

Literature Resources

| Publication title | Publication number |
|---|---------------------------|
| Agilent MXA Signal Analyzer | |
| <i>Agilent MXA Signal Analyzer, Brochure</i> | 5989-5047EN |
| <i>Agilent MXA Signal Analyzer, Data Sheet</i> | 5989-4942EN |
| <i>Agilent MXA Signal Analyzer, Configuration Guide</i> | 5989-4943EN |
| Agilent EXA Signal Analyzer | |
| <i>Agilent EXA Signal Analyzer, Brochure</i> | 5989-6527EN |
| <i>Agilent EXA Signal Analyzer, Data Sheet</i> | 5989-6529EN |
| <i>Agilent EXA Signal Analyzer, Configuration Guide</i> | 5989-6531EN |
| Agilent X-Series Signal Analyzers | |
| <i>Agilent X-Series Signal Analyzer (MXA/EXA), Demonstration Guide</i> | 5989-6126EN |
| <i>Agilent X-Series Signal Analyzers (MXA/EXA) W-CDMA, HSDPA/HSUPA, Technical Overview</i> | 5989-5352EN |
| <i>Agilent X-Series Signal Analyzers (MXA/EXA) 802.16 OFDMA, Technical Overview</i> | 5989-5353EN |
| <i>Agilent X-Series Signal Analyzers (MXA/EXA) Phase Noise, Technical Overview</i> | 5989-5354EN |
| <i>Agilent X-Series Signal Analyzers (MXA/EXA) GSM/EDGE, Technical Overview</i> | 5989-6532EN |
| <i>Using Agilent X-Series Signal Analyzers (MXA/EXA) for Measuring and Troubleshooting Digitally Modulated Signals, Application Note</i> | 5989-4944EN |
| <i>Using Agilent X-Series Signal Analyzers (MXA/EXA) Preselector Tuning for Amplitude Accuracy in Microwave Spectrum Analysis, Application Note</i> | 5989-4946EN |
| <i>Maximizing Measurement Speed with Agilent X-Series Signal Analyzers (MXA/EXA), Application Note</i> | 5989-4947EN |



Agilent Email Updates

www.agilent.com/find/emailupdates

Get the latest information on the products and applications you select.



Agilent Direct

www.agilent.com/find/agilentdirect

Quickly choose and use your test equipment solutions with confidence.



www.agilent.com/find/open

Agilent Open simplifies the process of connecting and programming test systems to help engineers design, validate and manufacture electronic products. Agilent offers open connectivity for a broad range of system-ready instruments, open industry software, PC-standard I/O and global support, which are combined to more easily integrate test system development.



www.lxistandard.org

LXI is the LAN-based successor to GPIB, providing faster, more efficient connectivity. Agilent is a founding member of the LXI consortium.

Microsoft® and Windows® are U.S. registered trademarks of Microsoft Corporation.

Pentium® is a U.S. registered trademark of Intel Corporation.

cdma2000 is a registered certification mark of the Telecommunications Industry Association. Used under license.

Remove all doubt

Our repair and calibration services will get your equipment back to you, performing like new, when promised. You will get full value out of your Agilent equipment throughout its lifetime. Your equipment will be serviced by Agilent-trained technicians using the latest factory calibration procedures, automated repair diagnostics and genuine parts. You will always have the utmost confidence in your measurements.

Agilent offers a wide range of additional expert test and measurement services for your equipment, including initial start-up assistance onsite education and training, as well as design, system integration, and project management.

For more information on repair and calibration services, go to:

www.agilent.com/find/removealldoubt

www.agilent.com

For more information on Agilent Technologies' products, applications or services, please contact your local Agilent office. The complete list is available at:

www.agilent.com/find/contactus

Americas

| | |
|---------------|----------------|
| Canada | (877) 894-4414 |
| Latin America | 305 269 7500 |
| United States | (800) 829-4444 |

Asia Pacific

| | |
|-----------|----------------|
| Australia | 1 800 629 485 |
| China | 800 810 0189 |
| Hong Kong | 800 938 693 |
| India | 1 800 112 929 |
| Japan | 0120 (421) 345 |
| Korea | 080 769 0800 |
| Malaysia | 1 800 888 848 |
| Singapore | 1 800 375 8100 |
| Taiwan | 0800 047 866 |
| Thailand | 1 800 226 008 |

Europe & Middle East

| | |
|----------------------|------------------------|
| Austria | 0820 87 44 11 |
| Belgium | 32 (0) 2 404 93 40 |
| Denmark | 45 70 13 15 15 |
| Finland | 358 (0) 10 855 2100 |
| France | 0825 010 700* |
| Germany | 01805 24 6333** |
| Ireland | 1890 924 204 |
| Israel | 972-3-9288-504/544 |
| Italy | 39 02 92 60 8484 |
| Netherlands | 31 (0) 20 547 2111 |
| Spain | 34 (91) 631 3300 |
| Sweden | 0200-88 22 55 |
| Switzerland (French) | 41 (21) 8113811(Opt 2) |
| Switzerland (German) | 0800 80 53 53 (Opt 1) |
| United Kingdom | 44 (0) 118 9276201 |

Other European Countries:
www.agilent.com/find/contactus

Revised: October 24, 2007

Product specifications and descriptions in this document subject to change without notice.

© Agilent Technologies, Inc. 2006, 2007
Printed in USA, October 29, 2007
5989-4942EN



Agilent Technologies