

CT3353

Coaxial Attenuator

Datasheet

N male to female Coaxial Attenuator, Instrument Grade

Description

Precision N Type male to female fixed coaxial attenuator.
Useful in a wide variety of applications including impedance matching and level control.

- High quality, rugged construction
 - Excellent VSWR
 - 2W power level
 - Useable to 12.4 GHz
 - Passivated Stainless Steel
-
- Available as 6 attenuator kit CT3417



Technical data subject to change.

© Cal Test Electronics 2018.

caltestelectronics.com



All specifications apply to the unit after a temperature stabilization time of 20 minutes over an ambient temperature range of 25°C ± 5°C.

Specifications

Attenuation	3 dB	6 dB
Attenuation (Voltage)	1.4x	2x
Accuracy	0.75 dB Max.	
Impedance, ohm	50	
Frequency Range	DC to 12.4 GHz	
VSWR Max	1.15:1 - DC to 4 GHz	1.25:1 - 4 to 12.4 GHz
Avg. Power	2 W	
Peak Power	500 W	
Temperature (degrees)	0 to +125C	
RoHS (2011/65/EU)	Compliant	

Specifications are subject to change without notice. To ensure the most current version of this manual, please download the current version from our website: caltestelectronics.com

Technical data subject to change.

© Cal Test Electronics 2018.

caltestelectronics.com

