



Please visit us at: www.valuetronics.com

Hipot - DCR Hybrid 2000

AC/DC/IR/DCR Analyzer

USES:

- Small Wire & Cable Testing
- Medical Component & Lead Testing
- Heater Production Testing
- Transformer Electrical Safety Testing
- Electric Motor Safety Testing
- Electronic Component Testing

FEATURES:

- Programmable Output Current to 30mA AC, 10mA DC
- Real and Total Current Measurement
- Programmable Output Voltage to 5kV AC 6kV DC
- Insulation Resistance Measurements from 1M Ω to 50G Ω
- DC Resistance Measurements from 10m Ω to 100k Ω
- Flex Test
- Ramp, Dwell, Test & Fall Times
- Programmable High & Low Limits
- Open/Short Circuit Check
- Arc Detection w/ Programmable Limit
- Storage of 50 Tests Setups with Multiple Steps per Measurement
- Front Panel Lockout
- RS232 Interface, Standard
- 8 Channel HV Scanner
- GFI

Introduction

The Hybrid 2000 Analyzer is a complete dielectric testing solution with AC Hipot, DC Hipot, Insulation Resistance and DC Resistance testing capability. The Hybrid 2000 combines these four test modes with eight HV scan channels for fast multi-point testing. The Hybrid 2000 has Open/Short Circuit detection for establishing proper device connection and Load/Line regulation to ensure measurement integrity. The digital display and user friendly controls allow test parameters and limits to be set without the high voltage activated.

Description

AC Hipot Capability for AC dielectric withstand testing. The test voltage can be programmed in the range from 50VAC to 5kVAC with a resolution of 1V. Measures both total and real current with output current capability to 30mA.

DC Hipot Capability for making DC dielectric withstand measurements. The test voltage can be programmed in the range from 50VDC to 6kVDC with a resolution of 1V. The maximum total current is 10mA.

Insulation Resistance Measurements for testing the dielectric strength and breakdown of electrical devices, components and materials. The IR measurement range is from 1M Ω to 50G Ω with test voltages from 50 to 5000VDC.

DC Resistance (DCR) Measurements for 2-wire/4-wire resistance testing. Perform multi-point DCR measurements from 10m Ω to 100k Ω . Set to continuous to monitor resistance while checking for intermittent connections.

DCR Balance is used to detect the balance of wound components such as motors. The DCR balance nominal value can be programmed from 0.001 Ω to 999 Ω . This function will compare DCR readings and prompt a failure if the variance in readings is greater than the set nominal value. This function will ensure good quality of the motor windings.

Sub Pass test mode is the only function on the market that provides sub step testing. Sub step will be activated if the main step fails This function will allow the end user to analyze the specific failure points from a mass test of the DUT.

Temperature Compensation function provides high accuracy for resistance measurements on application such as motor winding or coils with temperature correction.



For more detailed information on specifications, pricing and special purchase, rent and lease options, contact us at:

www.quadtech.com

Hybrid 2000

Please visit us at: www.valuetronics.com

AC Hipot

AC Output Voltage: Range: 50V to 5000V AC
 Resolution: 1Volts/step
 Frequency: 50/60 Hz selectable
 Waveform: Sinusoidal
 Accuracy: $\pm(1\%$ of setting +5V)
 Resolution: 1 Volt
 Accuracy: $\pm(1\%$ of reading + 5V)
 Resolution: 1 Volt
 Range: 0.001mA to 30mA AC
 Resolution: 1 μ A
 Accuracy: $\pm(1\%$ of reading + 5cnt) Total

High/Low Limit Test: Range: 0.001mA to 30mA AC
 Low limit can be turned OFF

Insulation Resistance

Insulation Resistance: Range: 1M Ω - 50G Ω
 1M - 1G: $\pm(3\%$ + 10 cts), $\geq 500V$
 1G - 10G: $\pm(7\%$ + 10 cts), $\geq 500V$
 10G - 50G: $\pm(10\%$ + 10 cts), $\geq 500V$

IR Output Voltage: Range: 50V to 5000V DC
 Accuracy: $\pm(1.5\%$ of setting +5V)

High/Low Limit Test: 1M Ω - 50G Ω
 High limit can be turned OFF

DC Resistance (DCR)

DC Resistance: Range: 10m Ω - 100k Ω

DCR Balance: 0.0001 Ω - 999 Ω , OFF

DC Hipot

DC Output Voltage: Range: 50V to 6000V DC
 Resolution: 1Volts/step
 Regulation: $\pm(1\%$ of setting +5V)

Voltage Display: Accuracy: $\pm(1\%$ of reading + 5V)
 Resolution: 1 Volt

DC Current Display: Range: 0.0001mA to 10mA DC
 3 Ranges: .0001mA - .2999mA,
 0.3mA - 2.999mA, 3mA - 10mA
 Accuracy: $\pm(1\%$ of reading + 5cnt)

High/Low Limit Test: 0.1 μ A to 10mA DC
 Low limit can be turned OFF

Charging Current: 10mA max

Common Features

Open/Short Detection: Voltage <100V, Frequency: 600Hz
 Open: 10-100%; Short: 100-500%

Arc Detection: Arc Level: adjustable OFF or
 .1mA - 15mA AC & 10mA DC
 Arc Duration: > 10 μ s

Indication: Pass/fail lights, audible sound

Time: Ramp: 0.1 to 999s (± 20 ms), OFF
 Dwell: 0.1 to 999s (± 20 ms), OFF
 Test: 0.3 to 999s (± 20 ms), Continuous
 Fall: 0.1 to 999s (± 20 ms), OFF
 Sub Pass: 0.01s - 0.5s

Quick Discharge: Discharge of voltage across DUT back
 through the HV transformer

Output Cutoff: <0.4msec after limit exceeded

Ground Fault Interrupt: Automatic instrument shutdown for
 current imbalance >0.5mA ± 0.25 mA AC

Standard Interfaces: RS232: 9-pin
 Interlock

Test Setups: 50 Memory Locations, 20 Steps

Scan Channels: 8 HV Scan Channels - 2 W Terminals Setup
 4 HV Scan Channels - 4 W Terminals Setup

Scan Test Cables: 8 Custom Banana to Alligator Clip

Connectors: 8 HV OUTPUT (Custom Banana)
 Programmable as High, Low or Off
 RTN/LOW (Binding Post)

Front Panel Lockout: Key press with or without memory recall

Miscellaneous: Zero Offset

Dimensions: (w x h x d): 17 x 6.8 x 17.7in
 (430x175x450mm)

Weight: 44 lbs (20kg) net, 50 lbs (22kg) ship

Environmental: Meets MIL-T-28800E, Type 3, Class 5
 Operating: 0°C to + 40°C
 Humidity: <70%
 Storage: - 10°C to + 60°C

Power: •90 - 130V AC •50 or 60Hz
 •200 - 250V AC •500W max

2 TERMINALS MEASURE	
Test range	Measurement Accuracy
050.0m Ω ~1.000 Ω	$\pm(2\%$ of reading + 0.5% of range)
0.010 Ω ~10.00 Ω	
9.00 Ω ~100.0 Ω	
90.0 Ω ~1.000k Ω	
0.900k Ω ~10.00k Ω	
9.00k Ω ~100.0k Ω	
4 TERMINALS MEASURE	
Test range	Measurement Accuracy
010.0m Ω ~1.000 Ω	$\pm(0.5\%$ of reading + 0.5% of range)
0.900 Ω ~10.00 Ω	$\pm(0.5\%$ of reading + 0.05% of range)
9.00 Ω ~100.0 Ω	
90.0 Ω ~1.000k Ω	
0.900k Ω ~10.00k Ω	
9.00k Ω ~100.0k Ω	

Ordering Information

Hybrid 2000 AC/DC/IR/DCR Analyzer

Includes:

150827 Instruction Manual
 700070 Power Cable
 S02 Test Leads
 700100 Ground Continuity Lead
 Lead Set: (8) HV Banana to Alligator
 520068 5A 250V Power Line Fuse
 520134 2.5A 250V Power Line Fuse
 Calibration Certificate Traceable to NIST

Optional Accessories:

Calibration Data
 S02 HV Lead Set, 1m, (std w/unit)
 S03 Corded Product Adapter(115V)
 S04 HV Lead Set, 2m
 S05 Foot Switch
 S06 High Voltage Probe
 S07 Power Entry Adapter Cable
 S08 Gun Probe
 S09 HV Lead, 1 meter, unterminated
 S10 HV Lead, 2 meters, unterminated

S11 Gun Probe with remote start
 S12 Load Box, resistive
 S14 Load Box, custom resistors
 G16 International Power Strip
 G25 Corded Product Adapter (240V)
 G40 Scanner Lead Set (8), with Clips
 850900 IEEE-488/Handler Interface
 2000-AB 8 to 16 Channel Scanner

Product Specifications

www.valuetronics.com

