

Features

Frequency Range 150 MHz to 230 MHz

Designed for IEC / EN 61000-4-6

Two unscreened, balanced pairs

Individual calibration included

Three Year Warranty



Description

Com-Power CDN-T4E is a part of the series of Coupling/Decoupling Networks designed specifically for testing product for conducted immunity per IEC/EN 61000-4-6.

The CDN-T4E is designed for testing products that uses two unscreened, balanced pairs for communication such as Ethernet. It has a RJ45 connectors for both EUT and AE connection. The CDN-T4E can handle up to 2 Amps of current.

The RF disturbance signal coupling port is female BNC. It can handle up to 40V of RF Input Voltage. The bottom surface of the CDN is not painted for easy and effective grounding.

All Com-Power CDNs are individually calibrated. The Com-Power CDN-T4E fully complies with the requirements contained in the IEC 61000-4-6 and CISPR 16-1-2.

All Com-Power CDNs can be purchased separately or as part of the CIS series conducted immunity test system. This is a pre-packaged solution that includes an ACS series power amplifier and all accessories required for the test.

Application

During conducted Immunity testing, CDNs are utilized to provide a means of coupling RF common mode signals to each line. In addition, CDNs provide the required common mode impedance to the EUT, isolation to the auxiliary equipment via common mode decoupling of the disturbance signals and provide uninterrupted communication between the EUT and auxiliary equipment.

Before you begin testing with the CDN-T4E you will need to establish calibrated drive levels corresponding to your desired test levels. During drive level calibration, the RF signal level being injected to the CDN is adjusted incrementally until the voltage level measured at the 150Ω to 50Ω adapter (ADA-515-2) connected to the EUT port of the CDN is approximately equal to the U_{mr} value given in the table below. The ADA-515-2 and accessories needed for this test are available from Com-Power.

Test Levels Open Circuit Voltage	U_{mr}
1	0.167
3	0.5
10	1.67

U_{mr} = Voltage level measured at the output of the 150Ω to 50Ω adapter (ADA-515-2)

Specifications

Product Name	Coupling Decoupling Network (CDN)
Compliant Test Standards	IEC / EN 61000-4-6
Application	Two unscreened, balanced pairs
Frequency Range	150 kHz to 230 MHz
RF Input Voltage	40V (Max)
RF Input Connector	50Ω BNC (Female)
Voltage Rating	124 VAC / 125 VDC (Line to Ground)
Current Rating	2 Amps (Max)
AE and EUT Connections	RJ 45
Common Mode Impedance	150 kHz - 26 MHz: $150\Omega \pm 20\Omega$ 26 MHz - 80 MHz: $150\Omega + 60\Omega / - 45\Omega$ 80 MHz - 230 MHz: $150\Omega + 60\Omega / - 60\Omega$
Voltage Division Factor	9.5 dB +4/-1
Decoupling of Common Mode Disturbance	150 KHz ≥ 45 dB (RF/AE) 500 KHz ≥ 50 dB (RF/AE) 230 MHz ≥ 50 dB (RF/AE)
Dimensions	8.5 x 4.5 x 3.5 inches 21.5 x 11.4 x 8.8 cm
Weight	2 lbs. 0.9 kg
Accessories Available from Com-Power for setting test levels and running the test	ADA-T4/T8 shorting adapters ADA-515-2 150Ω to 50Ω adapters TEP-050 50Ω Terminator 1, 3, 6, 10, 20, 30 dB Power Attenuators Directional Coupler ACS series Power Amplifiers



Shorting Adapter Set ADA-T4/T8





ADA-515-2 Adapter Set



TEP-050 Terminator

All values are typical values unless otherwise specified.
Specifications are subject to change without notice.

Typical Data



Rev. D01.14