

Automated
Test Handlers

Device Kits

Docking Interfaces

Thermal Products

Engineering •
Thermal Control

Environmental •
Test Chambers

Products: [Thermal Products:](#) [Environmental Test Chambers:](#) 9023



SPECIFICATIONS

Test Volume	0.37 cubic feet (10.5 liters)
Internal Dimensions	8"H x 10"W x 8"D (20.32 x 25.40 x 20.32 cm)
Overall Dimensions	12 ¾"H x 17 ½"W x 20 ¾"D (32.38 x 44.45 x 52.70 cm)
Temperature Range	-73°C to + 315°C or -100°F to + 600°F OPTION -184°C (-300°F) With optional LN2
Heat-up Rate	24°C / Minute
Cool-down Rate	31° C / Minute
LCO2 Consumption	5.6 lbs/hr at -53°C (-65°F)
Air Circulation	Vertical air flow pattern
Power Requirements	120 VAC, 50 or 60 Hz., single phase, 1800w 208 VAC, 50 or 60 Hz., three wire, single phase, 1800w 208 VAC, 50 or 60 Hz., four wire, single phase, 1800w 240 VAC, 50 or 60 Hz., single phase, 1800w
Net Wt. (Approx.)	47 lbs (21.3 Kg)
Shipping Wt. (Approx.)	60 lbs (27.2 Kg)
Door Options Available	Blank with Tray; Ten 3/8" Dia Ports with Tray; Window and Five 3/8" Dia Ports - No Tray

[Back to Environmental Test Chambers](#)