

Type K/J Single Input Thermometer

Side-Button Controls

For convenient one-hand operation

Features:

- Large backlit LCD display
- Wide temperature range with 0.1°/1° resolution
- Readout in °F, °C, or K (Kelvin)
- Data Hold function freezes reading on display
- Max/Min/Avg readings with relative time stamp
- Offset key used for zero function to make relative measurements
- Auto Power off with disable feature
- Complete with Type K bead wire temperature probe and 9V battery



TP875



TP200

Optional Accessories:

Model TP875 — Optional Type K Bead Wire Temperature Probe measures from -58 to 1000°F (-50 to 538°C) with subminiature connector. Includes a banana adaptor connector for use with meters with banana adaptor inputs.

Model TP200 — Optional Type K Pipe Clamp Temperature Probe for hands-free superheat/sub-cooling temperature measurement from -4°F to 200°F (-20°C to 93°C)

Visit www.extech.com for a wide selection of Temperature Probes including Penetration and Surface Probes.

Specifications

| | |
|----------------------|------------------------------------|
| Temperature (Type K) | -328 to 2501°F (-200 to 1372°C) |
| Temperature (Type J) | -346 to 2012°F (-210 to 1100°C) |
| Basic Accuracy | ±(0.15% rdg + 1°C) |
| Resolution | 0.1°/1° |
| Dimensions | 8.7 x 2.5 x 1.1" (220 x 63 x 28mm) |
| Weight | 7oz (200g) |

Ordering Information:

- TM100**Type K/J Single Input Thermometer
TM100-NIST ..Type K/J Single Input Thermometer w/ NIST Cert.
TP870Type K Bead Wire Temperature Probe (482°F/250°C)
TP875Type K Bead Wire Temperature Probe (1000°F/538°C)
TP200Type K Pipe Clamp Probe (200°F/93°C)
409996Soft Vinyl Pouch Carrying case

