

## P/N: VSS-20

### Copyright

© 2015, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

### Document identity

Publ. No.: VSS-20  
 Release:  
 Commit: 29700  
 Language: en-US  
 Modified: 2015-10-16  
 Formatted: 2015-10-20

### Website

<http://www.flir.com>

### Customer support

<http://support.flir.com>

### Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to [exportquestions@flir.com](mailto:exportquestions@flir.com) with any questions.



|                               |  |
|-------------------------------|--|
| Part No.                      | VSS-20   |
| <b>General information</b>    |  |
| Short description             | 20 m (66') plumbing spool (no camera, need VSC25 or VSC28) |
| Compatible main unit          | VS70   |
| Integrated handset            | No   |
| Wireless capabilities         | N/A  |
| Compatible wireless handset   | With optional VST  |
| Compatible detachable cameras | VSC25 or VSC28   |
| Warranty                      | 2 years  |
| <b>Camera specifications</b>  |  |
| Articulation                  | No   |
| Diameter                      | N/A  |
| Resolution                    | N/A  |
| Probe length                  | 20 m (66')   |
| Focal length                  | N/A  |
| Field of view                 | N/A  |
| Imaging sensor                | N/A  |
| Video format                  | N/A  |
| Brightness control            | N/A  |
| Lamp type                     | N/A  |
| <b>Power system</b>           |  |
| Power requirements            | N/A  |
| <b>Environmental data</b>     |  |
| Operating temperature         | -10 to 50°C (14-122°F)                                     |
| Operating humidity            | 80% maximum  |
| Storage temperature           | -40 to 80°C (-40 to 176°F)                                 |



## 20 m (66') plumbing spool (no camera, need VSC25 or VSC28)

**P/N: VSS-20**

© 2015, FLIR Systems, Inc.

#VSS-20; r. /29700; en-US

| <b>Physical data</b>             |   |
|----------------------------------|---|
| Weight                           | See shipping information                                      |
| Dimensions (H x W x L)           | See shipping information                                      |
| Material                         | PC-ABS, rubber hand grip, nylon strap                         |
| Color                            | Gray, black   |
| <b>Shipping information</b>      |   |
| Packaging type                   | Brown box with shipping labels                                |
| Packaging contents               | Brown box, hard case, spool                                   |
| Packaging weight                 | 4 kg  |
| Packaging dimensions (H x W x L) | 45 cm x 37 cm x 17 cm   |
| Carton weight                    | 9 kg  |
| Carton dimensions (H x W x L)    | 46 cm x 32 cm x 40 cm   |
| Carton quantity                  | 2   |
| EAN-13                           | 0793950406144   |
| UPC-12                           | 793950406144  |
| Country of origin                | TW  |
| Tariff code                      | 9013909000  |
| <b>Technical support</b>         |   |
| Website                          | <a href="http://support.flir.com">http://support.flir.com</a> |
| E-mail                           | <a href="mailto:TMSupport@flir.com">TMSupport@flir.com</a>    |
| Phone                            | 855-499-3662  |
| Repairs                          | <a href="mailto:repair@flir.com">repair@flir.com</a>          |