

# 525B Temperature/ Pressure Calibrator

Superior accuracy and functionality in  
an economical benchtop package



The Fluke Calibration 525B Temperature/ Pressure Calibrator gives you a workhorse combination of high accuracy and broad functionality for temperature and pressure instrument calibration. Compact and economical, the 525B has an interface for automated calibration, providing wide workload coverage in instrument shops and calibration labs, as well as in ATE applications.

The 525B is the most accurate Fluke Calibration temperature calibrator, sourcing and measuring a complete range of RTDs, thermocouples, and the YSI 400 thermistor. It also measures pressure covering common ranges from 1 inch (6900 Pa) of water up to 10,000 PSI (69 MPa) using the Fluke 700 Series and 525A-P Series Pressure Modules. Plus, the dc voltage and current specifications of the 525B

enable you to calibrate other process calibrators and a wide variety of other instruments with accuracy that rivals any calibrator in its price range.

### Key features:

- Simulates and measures all ANSI thermocouples, as well as L and U types, and provides cold junction compensation to enable calibration of a wide variety of thermocouple instrumentation.
- Direct input for storage of ITS-90 RTD constants.
- RTD source uncertainties to 0.03 °C.
- Direct measurement of all Fluke 700 Series and 525A-P Series Pressure Modules covering the most common pressure ranges from 1" H<sub>2</sub>O to 10,000 PSI.
- Converts easily to any pressure unit directly from the front panel or through remote communications.
- Sources dc voltage and current for multifunction workload coverage, enabling calibration of data loggers, strip chart recorders, multimeters, and other industrial instruments.
- Supports automation using Fluke Calibration's MET/CAL® Plus Calibration Management Software or custom automated programs with standard RS-232-C and IEEE-488 interface.
- Eight user programmable setpoints allow quick recall of values for Zero, Span and linearity checks during calibration.
- Programmable setpoint dwell times for automated calibration and troubleshooting.

## Technical Data

- Selectable internal or external CJC (Cold junction compensation) provides you with the ability to make exacting thermocouple measurements using remote junctions.
- Easy five-way binding posts for low-loss convenient hookup. Banana plug, screw terminal, spade lug, wraparound terminal, wire pass-through terminal.
- NIST-traceable calibration with data is included.

### At home in the cal lab

The 525B is a compact bench instrument well suited for traditional calibration laboratories with a large temperature workload. Its 0 to 100 V output and 0 to 100 mA current capabilities—plus its ability to serve as a highly-accurate pressure standard—make it a versatile performer.

### Filling the gap in the instrument shop

In process plant environments, instrument shop technicians responsible for maintaining the equipment pool need to calibrate and repair a wide range of instruments, transmitters, field calibrators, P/I converters, transducers, and temperature probes. With its ability to simulate almost any temperature sensor, precise pressure monitoring capability, and dc voltage and current accuracy rivaling any calibrator in its price range, the 525B fills the gap between lower accuracy handheld field calibrators and more expensive high-end multifunction calibrators.

## A good fit for ATE test applications

With precise calibration-grade instrument control enabled via an IEEE bus, the 525B is a hardworking addition to automated test systems in quality and manufacturing test applications requiring capabilities such as voltage and current sourcing, sensor simulation, and temperature monitoring and validation.

## Powerful functionality that is easy to use

From start to finish, the 525B is designed for ease of operation. The intuitive front panel design features large keypads and display that help reduce training time and make the 525B comfortable to use even for long periods of time. Plus, you can store frequently used constants for a variety of probes in memory for faster setup on the job.

## MET/CAL<sup>®</sup> Plus automates 525B calibration and documentation management

You can use the 525B with MET/CAL Plus calibration software (V.6.11 or later) to meet the stringent documentation and reporting requirements imposed by quality standards such as ISO 9000. MET/CAL Plus is a powerful software environment for creating, editing, testing, and documenting calibration procedures, and for performing automated calibrations.

At the core of MET/CAL Plus is MET/TRACK<sup>®</sup> software, a database management system for test and measurement assets created specifically to manage equipment. It enables you to track the information you need to maintain quality calibrations. And it supports the traceability and record-keeping requirements of modern quality and accreditation standards.

MET/TRACK provides you with a variety of standard report formats prepared with Crystal Reports<sup>™</sup> Professional, which is included with MET/CAL Plus. These report formats cover a wide range of information to help you meet many of your documentation

requirements, including those for ISO 9000 and similar quality standards. They report on forward and reverse traceability, allowing you to easily document traceability from any asset to the equipment calibrated. It even includes measurement uncertainty reporting to meet the requirements of ISO/IEC 17025.

## Pressure modules

An optional set of external pressure modules provides pressure measurement capability. The 525B can accept either the Fluke 700 Series or the 525A-P pressure modules. Both module types plug directly into the calibrator's front panel Lemo connector; the 525B firmware auto-detects the type and value of the attached module.

## World-class temperature and pressure calibration solutions

In addition to the 525B Temperature/Pressure Calibrator, Fluke Calibration offers a broad range of solutions in temperature and humidity calibration as well as pressure and flow calibration.

Fluke Calibration makes everything you need for calibrating temperature sensors including SPRTs, PRTs, thermistors, and thermocouples. The constant temperature baths and dry-block calibrators offer unmatched stability, and the primary temperature standards are used in national metrology institutes around the world. For precision thermometry, Fluke Calibration thermometer readouts and probes are exceptionally accurate and easy to use, and the 1620A "DewK" temperature and humidity data logger handles your environmental monitoring needs.

Fluke Calibration also offers a range of high-end products focusing on pressure and flow calibrators and standards. More than 30 national measurement institutes rely on Fluke Calibration pressure standards to establish their pressure references. Fluke Calibration pressure standards, transfer standards, pressure controller/calibrators and monitors are recognized

for their advanced features and the realistic specifications that are the hallmark of a true metrology company.

## Calibration service, repair, and support

Fluke Calibration provides extensive calibration support and service to maximize the value of your calibration investment. Our worldwide network of Calibration Centers has traceability to national standards. Service and support are just a telephone call or fax away. We offer fast, quality repair and calibration services including a module exchange program, comprehensive training, and full support in setting up your lab.

## General specifications

Warm-up time	Twice the time since last warmed up, to a maximum of 30 minutes
Settling time	Less than 5 seconds for all functions and ranges except as noted
Standard interface	Standard, RS-232; IEEE-488 (GPIB)
Temperature performance	Operating: 0 °C to 50 °C Calibration (tcal): 15 °C to 35 °C Storage: -20 °C to 70 °C
Electromagnetic compatibility	Meets CE requirements, including susceptibility
Temperature coefficient	Temperature coefficient for temperatures outside tcal +5 °C is 10 % of the 90 day specification (or 1 year, as applicable) per °C
Relative humidity	Operating: < 80 % to 30 °C, < 70 % to 40 °C, < 40 % to 50 °C Storage: < 95 %, non-condensing
Altitude	Operating: 3,050 m (10,000 ft) maximum Non-operating: 12,200 m (40,000 ft) maximum
Safety	EN 61010 Second, ANSI/ISA-S82.01-1994; CAN/CSA-C22.2 No. 1010.1-92, NRTL
Analog low isolation	20 V
EMC	Designed to comply with IEC 61326-1/1997 (EMC)
Line power	Line voltage (selectable): 100 V/120 V or 220 V/240 V Line frequency: 47 Hz to 63 Hz Line voltage variation: ± 10 % about line voltage setting
Power consumption	15 VA maximum
Dimensions	Height: 13.3 cm (5.25 in) plus 1.5 cm (0.6 in) four feet on bottom Width: 0.75 in standard rack width Depth: 47.3 cm (18.6 in) overall
Weight (without options)	4 kg (9 lb)

# Electrical Specifications

## DC Voltage Specifications, Output

Ranges <sup>[1]</sup>	Absolute Uncertainty, tcal ± 5 °C ± (ppm of output + μV)				Stability	Resolution	Maximum Burden <sup>[2]</sup>
	90 days		1 year		24 hours, ± 1 °C ± (ppm of output + μV)		
	0 to 100.000 mV	25	3	30			
0 to 1.00000 V	25	10	30	10	4 + 10	10 V	10 mA
0 to 10.0000 V	25	100	30	100	4 + 100	100 μV	10 mA
0 to 100.000 V	25	1 mV	30	1 mV	5 + 1 mV	1 mV	1 mA
TC Output							
-10 to 75.000 mV	25	3	30	3	5 + 2	1 μV	10 Ω

Notes:  
 [1] All outputs are positive only.  
 [2] Remote sensing is not provided. Output resistance is < 1 Ω.

Ranges	Noise	
	Bandwidth 0.1 to 10 Hz ± (ppm of output + μV p-p)	Bandwidth 10 Hz to 10 kHz (μV rms)
0 to 100.000 mV	1 μV	6 μV
0 to 1.00000 V	10 μV	60 μV
0 to 10.0000 V	100 μV	600 μV
0 to 100.000 V	10 ppm+1 mV	20 mV

## DC Current Specifications, Output

Ranges <sup>[1]</sup>	Absolute Uncertainty tcal ± 5 °C ± (ppm of output + μA)				Resolution	Maximum Compliance Voltage	Maximum Inductive Load
	90 days		1 year				
	0 to 100.000 mA	40	1	50			

Note:  
 [1] All outputs are positive only.

Ranges	Noise	
	Bandwidth 0.1 to 10 Hz p-p	Bandwidth 10 Hz to 10 kHz rms
0 to 100.000 mA	2000 nA	20 μA

## Resistance Specifications, Output

Ranges <sup>[1]</sup>	Absolute Uncertainty tcal ± 5 °C, ± Ω		Resolution	Allowable Current <sup>[2]</sup>
	90 days	1 year		
	5 to 400.00 Ω	0.012		
5 to 4.0000 kΩ	0.25	0.3	0.01 Ω	100 μA to 1 mA

Notes:  
 [1] Continuously variable from 0 to 4 kΩ.  
 [2] For currents lower than shown, the floor adder increases by Floor<sub>(new)</sub> = Floor<sub>(old)</sub> × I<sub>min</sub>/I<sub>actual</sub>.  
 For example, a 500 μA stimulus measuring 100 Ω has a floor uncertainty of 0.015 Ω × 1 mA/500 μA = 0.03 Ω.

## Resistance Specifications, Input

Ranges <sup>[1]</sup>	Absolute Uncertainty tcal ± 5 °C, ± (ppm of output + Ω)				Resolution	Stimulus Current
	90 days		1 year			
	5 to 400.00 Ω	20	0.0035	20		
5 to 4.00000 kΩ	20	0.0035	20	0.004	0.01 Ω	0.1 mA

Note:  
 [1] 4-wire mode.

## Thermocouple Specification, Output and Input

TC Type	Range (°C)		Absolute Uncertainty tcal ± 5 °C, ± (°C) <sup>[1]</sup>	
			Output/Input	
	Minimum	Maximum	90 days	1 year
B	600 °C	800 °C	0.42 °C	0.46 °C
	800 °C	1000 °C	0.39 °C	0.39 °C
	1000 °C	1550 °C	0.40 °C	0.40 °C
	1550 °C	1820 °C	0.44 °C	0.45 °C
C	0 °C	150 °C	0.25 °C	0.30 °C
	150 °C	650 °C	0.21 °C	0.26 °C
	650 °C	1000 °C	0.23 °C	0.31 °C
	1000 °C	1800 °C	0.38 °C	0.50 °C
E	1800 °C	2316 °C	0.63 °C	0.84 °C
	-270 °C	-100 °C	0.38 °C	0.50 °C
	-100 °C	-25 °C	0.16 °C	0.18 °C
	-25 °C	350 °C	0.14 °C	0.15 °C
J	350 °C	650 °C	0.14 °C	0.16 °C
	650 °C	1820 °C	0.16 °C	0.21 °C
	-270 °C	-100 °C	0.20 °C	0.27 °C
	-100 °C	-30 °C	0.18 °C	0.20 °C
K	-25 °C	150 °C	0.14 °C	0.16 °C
	120 °C	760 °C	0.14 °C	0.17 °C
	1000 °C	1200 °C	0.18 °C	0.23 °C
	-270 °C	-100 °C	0.25 °C	0.33 °C
L	-100 °C	-25 °C	0.19 °C	0.22 °C
	-25 °C	120 °C	0.14 °C	0.16 °C
	120 °C	1000 °C	0.19 °C	0.26 °C
	1000 °C	1372 °C	0.30 °C	0.40 °C
N	-200 °C	-100 °C	0.37 °C	0.37 °C
	-100 °C	800 °C	0.26 °C	0.26 °C
	800 °C	900 °C	0.17 °C	0.17 °C
	-270 °C	-100 °C	0.33 °C	0.40 °C
R	-100 °C	-25 °C	0.20 °C	0.24 °C
	-25 °C	120 °C	0.16 °C	0.19 °C
	120 °C	410 °C	0.14 °C	0.18 °C
	410 °C	1300 °C	0.21 °C	0.27 °C
S	-50 °C	250 °C	0.58 °C	0.58 °C
	250 °C	400 °C	0.34 °C	0.35 °C
	400 °C	1000 °C	0.31 °C	0.33 °C
	1000 °C	1760 °C	0.30 °C	0.40 °C
T	0 °C	250 °C	0.56 °C	0.56 °C
	250 °C	1000 °C	0.36 °C	0.36 °C
	1000 °C	1400 °C	0.30 °C	0.37 °C
	1400 °C	1750 °C	0.35 °C	0.46 °C
U	-270 °C	-150 °C	0.51 °C	0.63 °C
	-150 °C	0 °C	0.18 °C	0.24 °C
	0 °C	120 °C	0.13 °C	0.16 °C
	120 °C	400 °C	0.12 °C	0.14 °C
mV	-200 °C	0 °C	0.56 °C	0.56 °C
	0 °C	600 °C	0.27 °C	0.27 °C
		-10 to 75.000 mV		
Note:				
[1] Does not include thermocouple wire error.				

**RTD and Thermistor Specification, Output**

RTD Type	Range (°C)		Absolute Uncertainty tcal ± 5 °C, ± (°C) <sup>[1]</sup>	
	Minimum	Maximum	90 days	1 year
Pt 385, 100 Ω	-200 °C	-80 °C	0.03 °C	0.04 °C
	-80 °C	0 °C	0.04 °C	0.05 °C
	0 °C	100 °C	0.04 °C	0.05 °C
	100 °C	300 °C	0.03 °C	0.04 °C
	300 °C	400 °C	0.04 °C	0.04 °C
	400 °C	630 °C	0.04 °C	0.05 °C
	630 °C	800 °C	0.04 °C	0.05 °C
Pt 3926, 100 Ω	-200 °C	-80 °C	0.03 °C	0.04 °C
	-80 °C	0 °C	0.03 °C	0.04 °C
	0 °C	100 °C	0.03 °C	0.04 °C
	100 °C	300 °C	0.03 °C	0.04 °C
	300 °C	400 °C	0.03 °C	0.04 °C
Pt 3916, 100 Ω	-200 °C	-190 °C	0.03 °C	0.03 °C
	-190 °C	-80 °C	0.03 °C	0.04 °C
	-80 °C	0 °C	0.03 °C	0.04 °C
	0 °C	100 °C	0.03 °C	0.04 °C
	100 °C	260 °C	0.03 °C	0.04 °C
	260 °C	300 °C	0.03 °C	0.04 °C
	300 °C	400 °C	0.03 °C	0.04 °C
Pt 385, 200 Ω	-200 °C	-80 °C	0.31 °C	0.38 °C
	-80 °C	0 °C	0.32 °C	0.38 °C
	0 °C	100 °C	0.33 °C	0.39 °C
	100 °C	260 °C	0.33 °C	0.39 °C
	260 °C	300 °C	0.36 °C	0.43 °C
	300 °C	400 °C	0.36 °C	0.43 °C
	400 °C	600 °C	0.42 °C	0.50 °C
Pt 385, 500 Ω	-200 °C	-80 °C	0.13 °C	0.15 °C
	-80 °C	0 °C	0.13 °C	0.15 °C
	0 °C	100 °C	0.13 °C	0.16 °C
	100 °C	260 °C	0.14 °C	0.17 °C
	260 °C	300 °C	0.14 °C	0.17 °C
	300 °C	400 °C	0.15 °C	0.18 °C
	400 °C	600 °C	0.16 °C	0.19 °C
Pt 385, 1000 Ω	-200 °C	-80 °C	0.06 °C	0.07 °C
	-80 °C	0 °C	0.06 °C	0.08 °C
	0 °C	100 °C	0.07 °C	0.08 °C
	100 °C	260 °C	0.07 °C	0.08 °C
	260 °C	300 °C	0.07 °C	0.09 °C
	300 °C	400 °C	0.07 °C	0.09 °C
	400 °C	600 °C	0.08 °C	0.09 °C
Ni 120, 120 Ω	-80 °C	0 °C	0.02 °C	0.02 °C
	0 °C	100 °C	0.02 °C	0.02 °C
	100 °C	260 °C	0.01 °C	0.02 °C
Cu 427, 10 Ω <sup>[2]</sup>	-100 °C	260 °C	0.30 °C	0.38 °C
YSI 400	15 °C	50 °C	0.005 °C	0.007 °C

Notes:  
 [1] 2-wire output.  
 [2] Based on MINCO Application Aid No. 18.



## RTD and Thermistor Specification, Input

RTD Type	Range (°C)		Absolute Uncertainty tcal ± 5 °C, ± (°C) <sup>[1]</sup>	
	Minimum	Maximum	90 days	1 year
Pt 385, 100 Ω	-200 °C	-80 °C	0.011 °C	0.012 °C
	-80 °C	0 °C	0.018 °C	0.020 °C
	0 °C	100 °C	0.018 °C	0.020 °C
	100 °C	300 °C	0.027 °C	0.030 °C
	300 °C	400 °C	0.031 °C	0.035 °C
	400 °C	630 °C	0.042 °C	0.047 °C
	630 °C	800 °C	0.050 °C	0.057 °C
Pt 3926, 100 Ω	-200 °C	-80 °C	0.011 °C	0.011 °C
	-80 °C	0 °C	0.014 °C	0.015 °C
	0 °C	100 °C	0.018 °C	0.019 °C
	100 °C	300 °C	0.026 °C	0.029 °C
	300 °C	400 °C	0.031 °C	0.034 °C
	400 °C	630 °C	0.041 °C	0.046 °C
Pt 3916, 100 Ω	-200 °C	-190 °C	0.006 °C	0.006 °C
	-190 °C	-80 °C	0.011 °C	0.012 °C
	-80 °C	0 °C	0.014 °C	0.015 °C
	0 °C	100 °C	0.018 °C	0.019 °C
	100 °C	260 °C	0.025 °C	0.028 °C
	260 °C	300 °C	0.026 °C	0.029 °C
	300 °C	400 °C	0.031 °C	0.034 °C
	400 °C	600 °C	0.040 °C	0.045 °C
600 °C	630 °C	0.042 °C	0.047 °C	
Pt 385, 200 Ω	-200 °C	-80 °C	0.008 °C	0.009 °C
	-80 °C	0 °C	0.012 °C	0.013 °C
	0 °C	100 °C	0.015 °C	0.017 °C
	100 °C	260 °C	0.020 °C	0.022 °C
	260 °C	300 °C	0.050 °C	0.053 °C
	300 °C	400 °C	0.053 °C	0.057 °C
	400 °C	600 °C	0.070 °C	0.075 °C
600 °C	630 °C	0.071 °C	0.076 °C	
Pt 385, 500 Ω	-200 °C	-80 °C	0.007 °C	0.008 °C
	-80 °C	0 °C	0.019 °C	0.020 °C
	0 °C	100 °C	0.023 °C	0.025 °C
	100 °C	260 °C	0.030 °C	0.033 °C
	260 °C	300 °C	0.032 °C	0.035 °C
	300 °C	400 °C	0.037 °C	0.041 °C
	400 °C	600 °C	0.047 °C	0.052 °C
600 °C	630 °C	0.048 °C	0.053 °C	
Pt 385, 1000 Ω	-200 °C	-80 °C	0.011 °C	0.012 °C
	-80 °C	0 °C	0.014 °C	0.015 °C
	0 °C	100 °C	0.019 °C	0.020 °C
	100 °C	260 °C	0.025 °C	0.028 °C
	260 °C	300 °C	0.027 °C	0.030 °C
	300 °C	400 °C	0.030 °C	0.034 °C
	400 °C	600 °C	0.041 °C	0.045 °C
600 °C	630 °C	0.042 °C	0.047 °C	
PtNi 385, 120 Ω (Ni120)	-80 °C	0 °C	0.009 °C	0.010 °C
	0 °C	100 °C	0.010 °C	0.011 °C
	100 °C	260 °C	0.011 °C	0.012 °C
Cu 427, 10 Ω <sup>[2]</sup>	-100 °C	260 °C	0.067 °C	0.069 °C
YSI 400	15 °C	50 °C	0.005 °C	0.007 °C
SPRT	-200 °C	660 °C	0.05 °C	0.06 °C

Notes:  
 [1] 4-wire mode. Uncertainties listed do not include probe uncertainties.  
 [2] Based on MINCO Application Aid No. 18.

## 700 Series Pressure Modules Specifications

	Model	Range/Resolution	Range (approx)/Resolution	Reference <sup>1</sup> uncertainty (23 ± 3 °C)	High <sup>2</sup> side media	Low <sup>2</sup> side media	Fitting material
Differential	Fluke 700P00	1 in. H2O/0.001	0.25 kPa/0.0002	0.300 %	Dry	Dry	316 SS
	Fluke 700P01	10 in. H2O/0.01	2.5 kPa/0.002	0.200 %	Dry	Dry	316 SS
	Fluke 700P02	1 psi/0.0001	6900 Pa/0.7	0.150 %	Dry	Dry	316 SS
	Fluke 700P22	1 psi/0.0001	6900 Pa/0.7	0.100 %	316 SS	Dry	316 SS
	Fluke 700P03	5 psi/0.0001	34 kPa/0.001	0.050 %	Dry	Dry	316 SS
	Fluke 700P23	5 psi/0.0001	34 kPa/0.001	0.025 %	316 SS	Dry	316 SS
	Fluke 700P04	15 psi/0.001	103 kPa/0.01	0.025 %	Dry	Dry	316 SS
Gage	Fluke 700P24	15 psi/0.001	103 kPa/0.01	0.025 %	316 SS	Dry	316 SS
	Fluke 700P05	30 psi/0.001	207 kPa/0.01	0.025 %	316 SS	N/A	316 SS
	Fluke 700P06	100 psi/0.01	690 kPa/0.07	0.025 %	316 SS	N/A	316 SS
	Fluke 700P27	300 psi/0.01	2070 kPa/0.1	0.025 %	316 SS	N/A	316 SS
	Fluke 700P07	500 psi/0.01	3400 kPa/0.1	0.025 %	316 SS	N/A	316 SS
	Fluke 700P08	1000 psi/0.1	6900 kPa/0.7	0.025 %	316 SS	N/A	316 SS
Absolute	Fluke 700P09	1500 psi/0.1	10 M Pa/0.001	0.025 %	316 SS	N/A	316 SS
	Fluke 700PA3	5 psi/0.0001	34 kPa/0.001	0.050 %	316 SS	N/A	316 SS
	Fluke 700PA4	150 psi/0.001	103 kPa/0.001	0.050 %	316 SS	N/A	316 SS
	Fluke 700PA5	30 psi/0.001	207 kPa/0.01	0.050 %	316 SS	N/A	316 SS
Vacuum	Fluke 700PA6	100 psi/0.01	690 kPa/0.001	0.050 %	316 SS	N/A	316 SS
	Fluke 700PV3	-5 psi/0.0001	-34 kPa/0.001	0.040 %	316 SS	Dry	316 SS
Dual	Fluke 700PV4	-15 psi/0.001	-103 kPa/0.01	0.040 %	316 SS	Dry	316 SS
	Fluke 700PD2	± 1 psi/0.0001	± 6900 Pa/0.7	0.150 %	316 SS	Dry	316 SS
	Fluke 700PD3	± 5 psi/0.0001	± 34 kPa/0.001	0.040 %	316 SS	Dry	316 SS
	Fluke 700PD4	± 15 psi/0.001	± 103 kPa/0.01	0.025 %	316 SS	Dry	316 SS
	Fluke 700PD5	-15/30 psi/0.001	-100/207 kPa/0.01	0.025 %	316 SS	N/A	316 SS
	Fluke 700PD6	-15/100 psi/0.01	-100/690 kPa/0.07	0.025 %	316 SS	N/A	316 SS
High	Fluke 700PD7	-15/200 psi/0.01	-100/1380 kPa/0.1	0.040 %	316 SS	N/A	316 SS
	Fluke 700P29	3000 psi/0.1	20.7 M Pa/0.001	0.050 %	C276	N/A	C276
	Fluke 700P30	5000 psi/0.1	34 M Pa/0.001	0.050 %	C276	N/A	C276
	Fluke 700P31	10000 psi/1	69 M Pa/0.007	0.050 %	C276	N/A	C276

<sup>1</sup> Total uncertainty, one year for temperature range 0 °C to +50 °C. Total uncertainty, 1.0% of full span for temperature range -10 °C to 0 °C. For P00 module only, compensated temperature range is 15 °C to 35 °C. <sup>2</sup> "Dry" indicates dry air or non-corrosive gas as compatible media. "316SS" indicates media compatible with Type 316 Stainless Steel. "C276" indicates media compatible with Hastelloy C276. Use of pressure zero is required prior to measurement or source. Max overpressure specification includes common mode pressure. Modules are CE rated. Metric adapter(s): 1/4" NPr female to male BSP/ISO 1/4-19, tapered thread, included with all modules except P29, P30, and P31, all modules include a NIST traceable certificate and test data.

## 525A-P Series Precision Pressure Transducers

Type	Model	Range/Resolution	Range/Resolution	Reference Uncertainty (23 ± 3 °C)
Differential	525A-P02	1 psi/0.00001	6900 Pa/0.01	0.008 % FS
Gage	525A-P03	5 psi/0.00001	34 kPa/0.001	0.008 % FS
Gage	525A-P04	15 psi/0.001	103 kPa/0.001	0.008 % FS
Gage	525A-P05	30 psi/0.0001	207 kPa/0.001	0.008 % FS
Gage	525A-P06	100 psi/0.001	690 kPa/0.001	0.008 % FS
Gage	525A-P07	500 psi/0.001	3400 kPa/0.01	0.008 % FS
Gage	525A-P08	1000 psi/0.01	6900 kPa/0.01	0.008 % FS
Gage	525A-P29	3000 psi/0.01	20.7 M Pa/0.0001	0.008 % FS
Absolute	525A-PA4	15 psi/0.0001	103 kPa/0.001	0.008 % FS
Absolute	525A-PA5	30 psi/0.0001	207 kPa/0.001	0.008 % FS
Absolute	525A-PA6	100 psi/0.001	690 kPa/0.001	0.008 % FS
Absolute	525A-PA7	500 psi/0.001	3400 kPa/0.01	0.008 % FS
Absolute	525A-PA8	1000 psi/0.01	6900 kPa/0.01	0.008 % FS
Vacuum	525A-PV4	-15 TO 0 psi/0.0001	-34 kPa/0.001	0.008 % FS

# Pressure Measurement

The Calibrator can accept either the Fluke 700 or 525A-P series pressure modules. Pressure modules plug directly into the front panel Lemo connector with the Calibrator firmware autodetecting the type and value of the module you are attaching.

**Range** .....Determined by pressure module

**Accuracy/Resolution** .....Determined by pressure module

**Units**

- PSI .....pounds per square inch
- inH2O4°C .....inches of water at 4 degrees Celsius
- inH2O20°C .....inches of water at 20 degrees Celsius
- cmH2O4°C .....centimeters of water at 4 degrees Celsius
- cmH2O20°C .....centimeters of water at 20 degrees Celsius
- BAR .....bars
- mBAR .....millibars
- KPAL .....kilopascals
- inHG 0°C .....inches of mercury at 0 degrees Celsius
- mmHG 0°C .....millimeters of mercury at 0 degrees Celsius
- Kg/cm2 .....kilograms per square centimeter

Model	Description
525B	Temperature/Pressure Calibrator
<b>Software</b>	
MET/CAL Plus	Automated Calibration Software (IEEE-488 and RS-232)
<b>Accessories</b>	
5520A-525A/Leads	Thermocouple and test lead set 1 meter TC wire with male mini-plugs, All ANSI, L and U types; TC shorting plug; 1, 80AK-8001 TC adapter; 1, bead thermocouple type K; 1 meter shielded test lead with double banana plugs (M); 2, 30 A test leads, banana type connectors
Y525	19" Rack Mount Kit
Fluke 700PD3	Dual Pressure Module ± 5 psi / ± 34 kPa
Fluke 700P31	High Pressure Module 10000 psi/69 M Pa
Fluke 700P22	Differential Pressure Module 1 psi / 6900 Pa
Fluke 700P24	Differential Pressure Module 15 psi / 103 kPa
Fluke 700PD2	Dual Pressure Module ± 1 psi / ± 6900 Pa
Fluke 700P08	Gage Pressure Module 1000 psi / 6900 kPa
Fluke 700PA4	Absolute Pressure Module 15 psi / 103 kPa
Fluke 700P30	High Pressure Module 5000 psi / 34 M Pa
Fluke 700PD7	Dual Pressure Module -15/200 psi / -100/1380 kPa
Fluke 700P05	Gage Pressure Module 30 psi / 207 kPa
Fluke 700P06	Gage Pressure Module 100 psi / 690 kPa
Fluke 700P29	High Pressure Module 3000 psi / 20.7 M Pa
Fluke 700PD5	Dual Pressure Module -15 / 30 psi / -100 / 207 kPa
Fluke 700PV3	Vacuum Pressure Module -5 psi / -34 kPa
Fluke 700P23	Differential Pressure Module 5 psi / 34 kPa
Fluke 700PA5	Absolute Pressure Module 30 psi / 207 kPa
Model	Description
<b>Accessories continued</b>	

Fluke 700P03	Differential Pressure Module	5 psi / 34 kPa
Fluke 700PD6	Dual Pressure Module	-15/100 psi / -100/690 kPa
Fluke 700P04	Differential Pressure Module	15 psi / 103 kPa
Fluke 700PA6	Absolute Pressure Module	100 psi / 6900 kPa
Fluke 700P01	Differential Pressure Module	10.00 in. H2O / 2.5 kPa
Fluke 700PD4	Dual Pressure Module	± 15 psi / ± 103 kPa
525A-P02	Differential	1 psi/6900 Pa
525A-P03	Gage	5 psi/34 kPa
525A-P04	Gage	15 psi/103 kPa
525A-P05	Gage	30 psi/207 kPa
525A-P06	Gage	100 psi/690 kPa
525A-P07	Gage	500 psi/3400 kPa
525A-P08	Gage	1000 psi/6900 kPa
525A-P29	Gage	3000 psi/20.7 M Pa
525A-PA4	Absolute	15 psi/103 kPa
525A-PA5	Absolute	30 psi/207 kPa
525A-PA6	Absolute	100 psi/690 kPa
525A-PA7	Absolute	500 psi/3400 kPa
525A-PA8	Absolute	1000 psi/6900 kPa
525A-PV4	Vacuum	-15 to 0 psi/-34 kPa
<b>Support</b>		
MET/SUPPORT Gold	Software Support Program, one-year membership	
MET/SUPPORT GLDNNW	MET/SUPPORT Gold Program, up to four workstations, one-year membership	

**Fluke Calibration. Precision, performance, confidence.™**



Electrical	RF	Temperature	Pressure	Flow	Software
------------	----	-------------	----------	------	----------

**Fluke Corporation**  
 PO Box 9090, Everett, WA 98206 U.S.A.  
**Fluke Europe B.V.**  
 PO Box 1186, 5602 BD  
 Eindhoven, The Netherlands

**For more information call:**  
 In the U.S.A. (800) 443-5853 or  
 Fax (425) 446-5116  
 In Europe/M-East/Africa +31 (0) 40  
 2675 200 or  
 Fax +31 (0) 40 2675 222  
 In Canada (800)-36-FLUKE or  
 Fax (905) 890-6866  
 From other countries +1(425) 446-5500 or  
 Fax +1 (425) 446-5116  
 Web access: <http://www.fluke.com>

©2001-2012 Fluke Corporation.  
 Specifications subject to change without notice.  
 Printed in U.S.A. 6/2012 1611141D\_EN  
 Pub\_ID: 10884-eng Rev 02