



## SAFETY DATA SHEET

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Identifier:** FP-500 FLUX

**SDS Number:** SDS-4318

**Revised Date:** 16 JUNE 2018

**Product Use:** INDUSTRIAL USE – FLUX.

#### MANUFACTURER:

##### In America:

The Indium Corporation of America®  
34 Robinson Rd, Clinton, NY 13323  
Technical & Safety Information: (315) 853-4900  
Safety Information: [nswarts@indium.com](mailto:nswarts@indium.com)  
<http://www.indium.com>

#### EMERGENCY PHONE (TRANSPORTATION SPILL):

**CHEMTREC 24 hrs.**

**USA: 1 (800) 424-9300**

**Outside USA: +1 (703) 527-3887**

##### In Europe:

Indium Corporation of America (European Operations)  
7 Newmarket Ct.  
Kingston, Milton Keynes, UK, MK 10 OAG  
Information: +44 [0] 1908 580400

##### In China:

Indium Corporation (Suzhou) Co., Ltd  
No. 428 Xinglong Street  
Suzhou Industrial Park  
Suchun Industrial Square  
Unit No. 14-C  
Jiangsu Province, China 215126  
Information: (86) 512-6283-4900

##### In Asia:

The Indium Corporation of America  
Asia-Pacific Operations-Singapore  
29 Kian Teck Avenue  
Singapore 628908  
Information: +65 6268-8678

## 2. HAZARDS IDENTIFICATION

### PRIMARY ROUTES OF ENTRY:

\*Eye

\*Inhalation

\*Skin

\*Ingestion

NTP

### Carcinogen listed in

IARC

OSHA

\*Not Listed

GHS



Signal Word: Danger

### Hazard statement (s)

H225 Highly flammable liquid and vapor

H319 Causes serious eye irritation

H317 May cause an allergic skin reaction

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H336 May cause drowsiness or dizziness

### Precautionary statement(s)

P210 Keep away from heat/spark/open flames/hot surfaces – No Smoking

P240 Ground container and receiving equipment

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

P362 +P364 Take off contaminated clothing and wash before reuse

P301 + P314 IF SWALLOWED: Get Medical advice/attention if you feel unwell

P302 +P352 IF ON SKIN: Wash with plenty of soap and water

P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing

P305 +P351 IF IN EYES: Rinse cautiously with water for several minutes (15 mins)

Classification:

Isopropyl alcohol:

Flammable Liquid – (Category 2)

Eye irritant – (Category 2A)

Skin irritant- (Category 3)

Specific target organ systemic toxicity (single exposure) – (Category 3)- central nervous system

### POTENTIAL HEALTH EFFECTS:

**Eye Contact:** Vapors may be irritating, liquid may damage eye tissue. Do not allow material to come in contact with the eyes.

**Ingestion:** May cause irritation.

**Inhalation:** Vapor may cause headaches and or dizziness. May be irritating to the respiratory tract. Inhalation of rosin fumes may cause occupational asthma.

**Skin Contact:** Prolonged contact may cause irritation and dermatitis.

**Chronic:** Not established.

Target organ: kidneys/ nerves,

**NOTE:** The Indium Corporation does not recommend, manufacture, market or endorse any of its products for human consumption.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	% wt	CAS Registry #/EINECS			
ISOPROPANOL	85-90	67-63-0 /200-661-7			
( PROPAN-2-OL) (IPA) (ISOPROPYL ALCOHOL)					
		(US)	980	983	1225
		(EU)	-	999	1250
		(Canada)	-	983	1228
		(Singapore)	983	-	1230
		(Mexico)	-	980	1225
		(China)	-	350	700
ROSIN	10-12	8050-09-7(US)	N.E	N.E.	N.E.
		(EU)	0.05	-	0.15
ADIPIIC ACID	2-5	124-04-9	N.E.	N.E	N.E.

### 4. FIRST AID MEASURES

<b>Eye Contact:</b>	Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical attention if irritation persists.
<b>Ingestion:</b>	If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.
<b>Inhalation:</b>	Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention.
<b>Skin Contact:</b>	Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

### 5. FIRE FIGHTING MEASURES

<b>Flash Point:</b>	11C(54°F)	<b>Method:</b>	Closed Cup (Flammable)
<b>Auto-ignition Temperature:</b>	750F		
<b>Flammable Limits:</b>	Upper: 12 ; Lower 2.0		
<b>Extinguishing Media:</b>	Dry chemical, Water or CO <sub>2</sub> . Use extinguishers appropriate for the surrounding fire conditions.		
<b>Special Fire Fighting Procedures:</b>	Wear protective clothing and self - contained breathing apparatus. Use water to cool fire exposed containers. Flammable vapors may travel great distances to ignition source and flash back.		

## 6. ACCIDENTAL RELEASE MEASURES

**Spill or Leak Procedures:** DO NOT allow material to enter sewer system or waterway. Wear personal protective equipment. Eliminate sources of ignition. Ventilate area in accordance with regulations. Dispose of following all Federal, State and Local regulations. Absorbed product and place into proper container for disposal.

## 7. HANDLING AND STORAGE

**Handling Precautions:** Keep containers tightly closed when not in use. Use care to avoid spills. Wear personal protective equipment. Ground containers.

**Storage Precautions:** Store product in tightly capped original containers in a cool, dry area. Refer to product label for specific storage temperature requirements. Rotate stock to ensure use before expiration date on the label. Store away from sources of heat and flame.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering Controls:** Face velocity >2.1 cubic feet/minute in confined areas. Exhaust ventilation recommended to keep exposures as low as possible.

### Personal protection:

**Eyes:** Chemical safety glasses/goggles. Face shield for splash hazards.

**Respirator:** A NIOSH approved or EU compliant CE marked air-purifying respirator with a fume/organic chemical cartridge is recommended where airborne concentrations are expected to be elevated.

**Skin:** Compatible chemical resistant gloves. Use gloves such as nitrile, which are compatible with alcohol and rosin chemicals.

**Other:** Lab coat, eye-wash/shower in work area. Avoid the use of contact lenses in high fume areas.

**Work/Hygienic Practices:** Maintain good housekeeping. Clean up spills immediately. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Light Amber	<b>Boiling Point:</b>	180F
<b>Odor:</b>	Alcohol odor.	<b>Evaporation Rate:</b>	>1
<b>Specific Gravity:</b>	0.817	<b>pH:</b>	6
<b>Vapor Pressure:</b>	31 mm HG @ 25C	<b>Solubility in Water:</b>	Partial
<b>Vapor Density:</b>	>1 (air=1)	<b>% Volatiles by volume:</b>	85

## 10. STABILITY AND REACTIVITY

**General:** Stable.

**Conditions to Avoid:** Direct heat, open flames and storage in aluminum.

**Incompatible Materials:** Anhydrides, halogens, phosphorus, trichlorides, monomers, aldehydes

**Hazardous Decomposition / Combustion:** Carbon dioxide/carbon monoxide.

**Hazardous Polymerization:** Will not occur.

## 11. TOXICOLOGICAL INFORMATION

**Carcinogenicity:** National Toxicity Program **NTP:** No  
Occupational Safety & Health Administration **OSHA:** No  
International Agency for Research on Cancer **IARC:** No

**LD50:** Not established. **LC50:** Not established.

Chronic Toxicity: Prolonged or repeated exposure to rosin flux fume may cause workers to develop occupational asthma.

Isopropanol:

LD50 Oral – rat -5,045 mg/kg

LC50 Inhalation – rat -8h -16000 ppm

LD50 dermal – rabbit – 12,800 mg/kg

RTECS- Isopropanol NT8050000

## 12. ECOLOGICAL INFORMATION

Product not tested.

Isopropanol:

Toxicity to fish LC50 – Pimephales promelas (fathead minnow) – 9640 mg/l – 96h

EC50 – Daphnia (water flea) – 5,102 mg/l – 24h

## 13. DISPOSAL CONSIDERATION

**Waste Disposal Method:** Dispose of in accordance with all Federal, State and Local environmental regulations. Disposal classification as flammable material.

## 14. TRANSPORT INFORMATION

Transport in accordance with applicable international regulations and requirements. Flammable material.

Shipping: UN1219, Isopropanol, 3, PG II



North America Emergency Guide Book – Guide #129

Marine pollutant: No

Shipping small quantities: Ground ONLY

40 CFR 173.150 - Exceptions for Class 3 (Flammable Liquids). Limited quantities of flammable liquids, Class 3, are excepted from labeling requirements for ground shipment only. For Packing Group II, inner packaging not over 5.0L (1.3 gallons) net capacity each, packed in a strong outer packaging.

40 CFR 172.203 – Limited quantities- when a shipping paper is required the description for a material offered for transportation as “limited quantity” must include the words “Limited Quantity” following the basic description.

Shipping: UN 1219, Isopropanol, 3, PG II (Limited Quantity) (mixture)

Review 40 CFR for clarification and further information.

Shipping via aircraft requires compliance with the regulations and not under exceptions.

## 15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

Some additional information is in accordance with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).

Canadian WHMIS: Class B Division 2 Flammable, D2B Toxic Material Causing Other Toxic Effects (eye irritation in animals).



This product has been classified in accordance with the guidelines set by the Dept. of Industrial Health of the Republic of Singapore.

SARA 313 Listing - 40 CFR 372.65: None

All ingredients are listed on the EPA TSCA Inventory.

This product has been classified under the Mexican regulations NOM-018-STPS-2015 and NOM-010-STPS-2014.

### Malaysia:

This product has been classified in accordance with: Malaysian – OCCUPATIONAL SAFETY AND HEALTH (CLASSIFICATION, LABELING AND SAFETY DATA SHEET OF HAZARDOUS CHEMICALS) REGULATION OCTOBER 2013 – (CLASS). (GHS)

### In China:

Decree No. 591: Regulations on the Control over Safety of Hazardous Chemicals  
GB 30000.2-29-2013, Rules for classification and labeling of chemicals. (GHS)  
GB/T 16483-2008, GB/T 17517-2013

This product has been classified using the Chinese Occupational Exposure Limit for Hazardous Agents in the Workplace, GBZ2-2007.

**16. OTHER INFORMATION**

<b>HMIS Hazard Rating:</b>	<b>Health:</b>	2
	<b>Fire:</b>	3
	<b>Reactivity:</b>	0

**Revised Date:** 16 JUNE 2018

**Prepared by:** Nancy Swarts, The Indium Corporation of America

**Approved by:** Nancy Swarts, The Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.