



GW Instek GDM-8255A/8251A portable precision multimeters engage with 5 1/2 digits, dual-display, 0.012% high DC voltage accuracy and various advanced measuring function to make electrical relative signal measurement faster and easier. In addition, the standard RS-232 and USB device make the GDM-8255A/8251A an ideal tool and inexpensive solution for field service, development/maintenance, education and ATE system applications.

## Various Measuring Functions

GDM-8255A/ 8251A provide 9 major measuring functions such as DCV/ACV, DCI/ACI, 2w/4w Resistance, Diode, Frequency, Continuity test and Temperature. The 0.012% DC voltage accuracy provides user the best measuring precision at the DC voltage applications. In addition, there are several advanced measuring functions such as Max, Min, dB, dBm, REL/REL#, Hold, Compare and Math functions to enhance the serviceability of measuring results.

## Combinational Dual Display

The GDM-8255A/ 8251A offer varieties of dual display combinations with main measurement function which allows the GDM-8255A/8251A to measure two properties of input signal. The dual display function can save customers measuring time when dealing with applications require multiple parameters simultaneously.

## Standard Multiple Interfaces

GDM-8255A/ 8251A provide the standard multiple interfaces for PC connection: RS232C and USB device port. Unlike the common RS232 transfer speed, the GDM-8255A/8251A even raises the baud rate up to 115200 which is 12 times faster.

It makes the command or data flow faster and smoother.

In addition, the digital I/O terminal outputs the result of comparison measurements to control external devices for ATE applications. By providing an independent VCC for the terminal, the digital I/O outputs can also be used as power source for TTL or CMOS logics.

## Convenient Remote Control & Data Capture

For a convenient remote control and a long data capture, the GDM-8255A/8251A accompanies free software, DMM-Viewer. This software allows users to remotely control the GDM-8255A/8251A without entering extra commands. Besides, the software interface and even the measurement method resemble those of GDM-8255A/GDM-8251A front panel, thus guaranteeing safe operation and shortened training and program development time.

For data capturing through a PC, the software allows users to observe measuring result before saving it as a file for further study. In addition, the saved data can be reloaded for converting into a graph. With the DMM-Viewer PC software, the user operation of GDM-8255A/8251A can be much more effective.

## Good Training tool for Education

The PC software, DMM-Viewer, is designed using a graphical user interface. With this kind design, users can easily operate as they work with unit. Besides, the DMM-Viewer could be operated as a training tool while it dose not communicate with GDM-8251A/8255A. It is beneficial for a class teaching of digital multimeter.

## GDM-8255A (199999 Counts) GDM-8251A (120000 Counts)

### FEATURES

- GDM-8255A : 199999 Counts Display  
GDM-8251A : 120000 Counts Display
- VFD , Two Colors Display
- Auto/Manual Ranging
- 2/4 Wire Resistance Measurement
- Temperature Measurement
- True RMS (AC, AC+DC)
- Selectable Measurement Rate
- Frequency Measurement
- Max./Min., REL, dBm, Compare, Math, Store, Recall, dB

### APPLICATIONS

- Products maintenance & development
- Circuit repair & debug
- Auto test equipment
- Education experiment & training



**GW INSTEK**

Made to Measure

**GDM-8255A/8251A**

**www.valuetronics.com**

SPECIFICATIONS			
		GDM-8255A	GDM-8251A
FULL SCALE		199999 Counts	120000 Counts
SAMPLE RATE		Slow : 5 1/2 digits, 10 readings/second Medium : 4 1/2 digits, 30 readings/second Fast : 3 1/2 digits, 60 readings/second	
DC VOLTAGE	Range Accuracy Input Impedance	100mV, 1V, 10V, 100V, 1000V 5 ranges ± (0.012% rdg + 5 digits) 10MΩ	
AC VOLTAGE True RMS	Range Accuracy  Input Impedance	100mV, 1V, 10V, 100V, 750V 5 ranges 20Hz~45Hz :± (1% rdg + 100 digits) 45Hz ~ 10kHz :± (0.2% rdg + 100 digits) 10kHz ~ 30kHz :± (1% rdg + 100 digits) 30kHz~100kHz :± (3% rdg + 200 digits) 1.1MΩ in parallel with approx. 100pF	
DC CURRENT	Range Accuracy	10mA, 100mA, 1A, 10A 4 ranges 10mA , 100mA :± (0.05% rdg + 15 digits) 1A, 10A range :± (0.2% rdg + 5 digits)	
AC CURRENT True RMS	Range Accuracy	10mA, 100mA, 1A, 10A 4 ranges 10mA , 100mA range : 20Hz ~ 50Hz :± (1.5% rdg + 100 digits) 50Hz ~ 10kHz :± (0.5% rdg + 100 digits) 10kHz~20kHz :± (2% rdg + 200 digits) 1A , 10A range : 50Hz ~ 10kHz :± (1% rdg + 100 digits)	
RESISTANCE	Range 2W Accuracy  4W Accuracy	100Ω , 1kΩ , 10kΩ , 100kΩ , 1MΩ , 10MΩ , 100MΩ 7 ranges 100Ω range :± (0.1% rdg + 8digits) (*);1kΩ range : ±(0.08% rdg + 5 digits) (*); 10kΩ ~ 1MΩ 3 ranges : ±(0.06% rdg + 5 digits) 10MΩ range :± (0.3% rdg + 5 digits); 100MΩ range ± (3% rdg + 8 digits) 100Ω range :± (0.05% rdg + 8digits) (*);1kΩ ~ 1MΩ 4 ranges : ±(0.05% rdg + 5 digits) 10MΩ range :± (0.3% rdg + 5 digits); 100MΩ range ± (3% rdg + 8 digits)	
DIODE TEST	Open Circuit Voltage Approx.2.0V, Test Current 0.5mA		
FREQUENCY	10Hz~800kHz		
CONTINUITY BEEPER	1 ~ 1000Ω Define by user		
TEMPERATURE	0° C ~ 300° C : J , K , T Type		
OTHER FUNCTIONS	Auto range / Manual, Math : MX + B/ % / 1/X Max, Min, dBm, dB, REL, Hold, Compare, Store, Recall		
DISPLAY	VFD, Two Colors Display		
INTERFACE	Digital I/O, USB Device, RS-232C		
DIMENSIONS & WEIGHT	265(W) x 107(H) x 350(D) mm, Approx. 2.6 kg		

Note : (\*)USE "REL" Mode

Specifications subject to change without notice. DM-8255AGD2DH

## ORDERING INFORMATION

**GDM-8255A** 199999 Counts Dual Display Digital Multimeter

**GDM-8251A** 120000 Counts Dual Display Digital Multimeter

### ACCESSORIES :

Quick start user manual x 1, Power cord x 1, Test lead GTL-117 x 1, CD x 1 (including complete user manual and PC software DMMViewer)  
Calibration key GDM-01 x 1 (Compatible with Fluke 5720A/5725A calibrators only)

## OPTIONAL ACCESSORIES

**GTL-108A** 4W Type test lead

**GTL-232** RS232C Cable, 9-pin Female to 9-pin, null Modem for Computer

**GTL-245** USB Cable

Global Headquarters

### GOOD WILL INSTRUMENT CO., LTD.

No. 7-1, Jhongsing Road, Tucheng City, Taipei County 236, Taiwan  
T +886-2-2268-0389 F +886-2-2268-0639  
E-mail: marketing@goodwill.com.tw

China Subsidiary

### INSTEK ELECTRONIC (SHANGHAI) CO., LTD.

8F, of NO.2 Building, No.889 Yishan Road, Shanghai China  
T +86-21-6485-3399 F +86-21-5450-0789  
E-mail: marketing@instek.com.cn

Malaysia Subsidiary

### GOOD WILL INSTRUMENT (M) SDN. BHD.

27, Persiaran Mahsuri 1/1, Sunway Tunas,  
11900 Bayan Lepas, Penang, Malaysia.  
T +604-6309988 F +604-6309989  
E-mail: sales@goodwill.com.my

U.S.A. Subsidiary

### INSTEK AMERICA CORP.

3661 Walnut Avenue Chino, CA 91710, U.S.A.  
T +1-909-5918358 F +1-909-5912280  
E-mail: sales@instek.com

Japan Subsidiary

### INSTEK JAPAN CORPORATION

4F, Prosper Bldg, 1-3-3 Iwamoto-Cho Chiyoda-Ku,  
Tokyo 101-0032 Japan  
T +81-3-5823-5656 F +81-3-5823-5655  
E-mail: info@instek.co.jp

Korea Subsidiary

### GOOD WILL INSTRUMENT KOREA CO., LTD.

Room No.805, Ace Hightech-City B/D 1Dong,  
Mullae-Dong 3Ga 54-66, Yeongduengpo-Gu, Seoul, Korea  
T +82-2-3439-2205 F +82-2-3439-2207  
E-mail : sales@gwinstek.co.kr

**GW INSTEK**

www.gwinstek.com.tw