

Function Generator

B1



GFG-8216A (3MHz)

GFG-8215A (3MHz)

FEATURES

- * Frequency Range: 0.3Hz ~ 3MHz
- * Waveforms: Sine, Triangle, Square, Ramp, TTL and CMOS Output
- * External Voltage Controlled Frequency (VCF) Function
- * Duty Cycle Control with Signal Inversion Capability

- * Variable DC Offset Control
- * Two-Step (-20dBx2) and Variable Attenuator
- * Built-In 6 Digit Counter with INT/EXT Function Up to 150MHz / High Resolution(GFG-8216A)

SPECIFICATIONS

MAIN

Frequency Range	0.3Hz ~ 3MHz (7 Range)
Amplitude	> 10Vpp (into 50Ω load)
Impedance	50Ω ±10%
Attenuator	-20dB ± 1dBx2
DC Offset	<-5V ~ >5V (into 50Ω load)
Duty Control	80% : 20% : 80% to 1MHz Continue variable
Display	6 digit LED display
Range Accuracy	*GFG-8215A does not have display. ± 5%+1Hz (at 3 position) for GFG-8215A

SINE WAVE

Distortion	≤ 1%, 0.3Hz ~ 200kHz
Flatness	< 0.3dB, 0.3Hz ~ 300kHz < 0.5dB, 300kHz ~ 3MHz

TRIANGLE WAVE

Linear	≥ 98%, 0.3Hz ~ 100kHz ≥ 95%, 100kHz ~ 3MHz
--------	---

SQUARE WAVE

Symmetry	± 2%, 0.3Hz ~ 100kHz
Rise or Fall Time	≤ 100nS at maximum output (into 50Ω load)

CMOS OUTPUT

Level	4Vpp ± 1Vpp ~ 14.5Vpp ± 0.5Vpp adjustable
Rise or Fall Time	≤ 120nS

TTL OUTPUT

Level	≥ 3Vpp
Fan Out	20 TTL load
Rise or Fall Time	≤ 25nS

VCF

Input Voltage	0V ~ 10V ± 1V (100 : 1)
Input Impedance	10kΩ ± 10%

FREQUENCY COUNTER(For GFG-8216A Only)

INT./EXT.	Switch selector
Range	0.3Hz ~ 3MHz (5Hz ~ 150MHz EXT.)
Accuracy	Time base accuracy ± 1 count
Time Base	± 20ppm(23° C ± 5° C) after 30 minutes warm up
Resolution	The maximum resolution is 100nHz for 1Hz and 1Hz for 100MHz
Input Impedance	1MΩ // 150pF
Sensitivity	≤ 35mVrms (5Hz ~ 100MHz) ≤ 45mVrms (100MHz ~ 150MHz)

POWER SOURCE

AC115V/230V ± 15%, 50/60Hz

ACCESSORIES

Instruction manual x 1, Power cord x 1, GTL-101 x 2;
GTL-101x1 for GFG-8215A

DIMENSIONS & WEIGHT

251(W) x 91(H) x 291(D)mm, Approx. 2.1kg

ORDERING INFORMATION

GFG-8216A	3MHz Function Generator with 6Digit LED Display
GFG-8215A	3MHz Function Generator