Patent No: 81011



## **FEATURES**

- \* Triple Output
- \* Auto Tracking
- \* Auto Series and Parallel Operation
- \* Constant Voltage and Constant Current Operation
- \* Low Ripple and Noise
- \* Two Digital Panel Meters
- \* Internal Select for Continuous or Dynamic Load
- \* Overload and Reverse Polarity Protection
- \* 5V, 3A Fixed Output

## GPC-6030D/3060D

## **SPECIFICATIONS**

#### **OPERATION MODE**

Series

Independent Two independent outputs and 5V fixed output

Output from 0 to rating volts and 0 to rating amperes Output from 0 to  $\pm {\rm rating}$  volts at rating amperes each

Output from 0 to double rating volts at rating amperes Output from 0 to double rating amperes at rating volts Parallel

#### **5V FIXED OUTPUT**

Regulation

Line regulation≤5mV Load regulation ≤10mV

Ripple & Noise ≤2mVrms Voltage Accuracy 5V±0.25V **Output Current** 

## TRACKING OPERATION

 $\leq$ 0.5% + 10mV of the master  $\leq$ 300mV **Tracking Error** 

Series Regulation

## **CONSTANT VOLTAGE OPERATION**

Line regulation ≤0.01% + 3mV Regulation

Load regulation ≤ 0.01% + 5mV(rating current < 10A) ≤ 0.02% + 5mV(rating current ≥ 10A)

≤1mVrms 5Hz ~ 1MHz Ripple & Noise

Recovery Time  $\leq$  100  $\mu$  S ( 50% Load change, Minimum load 0.5A )

# CONSTANT CURRENT OPERATION

Line regulation ≤0.2% + 3mA Regulation

Load regulation ≤0.2% + 3mA

**Ripple Current** ≤3mArms

**METER** Digital

3 1/2 digits 0.5" LED display Accuracy±( 0.5% of rdg + 2 digits )

INSULATION Chassis and Terminal  $\,$  100M $\!\Omega$  or above ( DC 1000V )

### Chassis and AC Cord 100M $\Omega$ or above (DC 1000V)

**POWER SOURCE** AC 100V/120V/220V/240V $\pm$ 10%, 50/60Hz

#### **ACCESSORIES**

Instruction manual x 1, Power cord x 1

Test lead GTL-105 x 1 ( $\leq$  3A), GTL-104 x 2 ( $\leq$ 10A)

#### **DIMENSIONS**

255(W) x 145(H) x 420(D) mm

ORDERING INFORMATION					
Model		Independent	Series	Parallel	Weight (kg)
GPC-6030D	375W D.C. Power Supply	(0 ~ 60V/0 ~ 3A) x 2 , (5V/3A MAX) x 1	120V 3A	60V 6A	18.5
GPC-3060D	375W D.C. Power Supply	(0 ~ 30V/0 ~ 6A) x 2 , (5V/3A MAX) x 1	60V 6A	30V 12A	18.5