

AC Millivolt Meter

D3



FEATURES

- * 300 μ V Full scale sensitivity
- * Measures frequency from 10Hz ~ 1MHz
- * Measures from -70dB ~ +40dB in 12 ranges
- * Dual Channel (GVT-427B)

GVT-427B(2CH)/GVT-417B(1CH)

SPECIFICATIONS

INPUT

Voltage Range	300 μ V~100V of Full Scale in 12 ranges
Decibel Range	-70dB ~ +40dB in 12 ranges
Accuracy	$\pm 3\%$ of full scale
Operating Mode	Channel 1 and 2 separately or simultaneously at channel 1 one channel only (GVT - 417B)
Frequency Responses	20Hz~200kHz $\pm 3\%$, 10Hz~1MHz $\pm 10\%$ (reference 1 kHz)
Impedance	1M Ω , approx, 40pF

OUTPUT

Level	Approx. 0.1Vrms at full scale
Distortion	Less than 2%

POWER SOURCE

AC 115/230V $\pm 10\%$, 50/60Hz

ACCESSORIES

Instruction Manual x 1
Power cord x 1
Test Lead GTL-101 x 2
(GTL-101 x 1 for GVT - 417B)

DIMENSIONS & WEIGHT

130(W) x 210(H)x295(D)mm; Approx. 2.7 kg

ORDERING INFORMATION

GVT-427B	2 Channels AC Millivolt Meter
GVT-417B	1 Channel AC Millivolt Meter

NOTE :  mark is only for GVT-417B