

Products

Service

About GW

Brand Origin

Contact Us

Membership

Accessories

Test Leads / Cables / Probes

Adaptors

LCR Fixtures

Cases / Bags / Racks

Special Applications

ATA-001

ATA-002

GAP-801

GAP-802

GDM-01

GDM-SC1

GHT-106R

GKT-001

GKT-002

GKT-003

GKT-006A

GPS-001

GRC-1201

GTC-001

GTC-002

RLB-001

TL-06

RLB-001

SHARE

PRINT

Features

- * 1GHz Return Loss Bridge
- * N-Type Connector, Source/Load:Female, Couple:Male
- * Impedance : 50 ohms
- * 88 x 54 x 32(mm), 230g
- * For : GSP-Series



Description	Specification	Accessories	Ordering Information	Download
PARAMETER				
Frequency Range	10MHz ~ 1GHz			
Directivity	10MHz ~ 100MHz: > 48dB 100MHz ~ 1000MHz: > 38dB			
Insertion Loss	Source to Load: < 10dB Load to Coupler: < 6dB			
Return Loss	Source Return Loss: > 7dB Load Return Loss: > 11dB Coupler Return Loss: > 11dB			
Characteristic Impedance	50 ohm			
Connector	N Type Source and Load: Female Coupler: Male			
Dimension & Weight	88(W) x 54(H) x 32(D) mm 230g			

Product Search

Please input keyword

SEARCH

Sales Contact