

LT300

High current loop testers



- High current loop tester
- Single and 3 phase testing
- 16 Hz to 400 Hz operation
- CATIV 300 V applications
- Two wire lead set or mains plug leads
- Tough armoured case

DESCRIPTION

The LT300 offers high current loop testing over a wide range of frequencies and supply voltages with simple, fast, two wire operation.

It has a large clear display that aids visibility in poor conditions.

Two models are available:

LT300-EN-00 - with red/green leads

LT300-EN-BS - with BS1363 mains plug lead

LT300-EN-FS - with fused red/green leads

The high current loop test provides fast accurate and stable results with a resolution to 0.01 Ω on the 20 Ω range.

Frequency range

Supply frequency is indicated upon connection to the supply. This will automatically set to the measured supply frequency either 16 Hz, 50/60 Hz or 400 Hz. Testing will commence automatically.

Loop Impedance measurement:

Two loop impedance ranges are provided.

20 Ω - Resolution to 0.01 Ω

200 Ω - Resolution to 0.1 Ω

Supply voltage:

Operational supply range extends from 50 V to 550 V (400 V @ 16 Hz), with a warning for voltages over 330 V highlighting accidental phase to phase connections on a nominal 230 V system.

Single Phase CATIV 300 V phase to earth, as well as 550 V phase to phase applications (400 V @ 16 Hz)

GENERAL 1

The instrument is housed in a rubber armoured case with a built-in cover to protect the display when not in use.

The IP54 weatherproof rating provides excellent protection in adverse conditions.

The instrument is supplied with either a two wire (red/green) lead set, or a mains plug test lead for access to wall sockets, a certificate of test and a hard carry case.

SPECIFICATION

Voltage measurement range

Voltage range: 0 V to 550 V (400 V @ 16 Hz)

Accuracy: ±5% ±2 V

Loop test operating frequencies

16 Hz 15 Hz to 18 Hz, 33 Hz, 29 Hz to 337 Hz

50/60 Hz 40 Hz to 70 Hz, 125 Hz, 100 Hz to 142 Hz

400 Hz 260 Hz to 498 Hz

Test currents

20 ½ Range 200 ½ Range

550 V 27 A 2.7 A

230 V 12 A 1.2 A

115 V 6 A 0.6 A

50 V 3 A 0.3 A

Loop test accuracy

Loop resistance:

0 to 19.99 ½ (20 ½ range) ±5% ±0.03 ½

0 to 199.9 ½ (200 ½ range) ±5% ±0.5 ½

Environmental

Operating temperature: -10°C to +60°C

Storage temperature: -25°C to +70°C

Humidity: 90%RH @+40°C

Maximum altitude: :2,000 m

Dust and water: IP54

Battery: 8 x AA (LR6) alkaline or NiMH rechargeable cells.

Safety

Meets the requirements of IEC61010-1 300 V CATIV phase to earth or 550 V Phase to Phase (400 V @ 16 Hz).

EN61557

Complies with the following parts of EN61557, Electrical safety in low voltage systems up to 1000 V a.c. and 1500 V d.c. Equipment for testing, measuring or monitoring of protective measures:

Part1 - General Requirements

Part3 - Loop resistance

EMC

In accordance with IEC61326-1

Weight: 980gms (2.16lb)

Dimensions: 203 x 148 x 78mm (8 x 5.8 x 3 in)



ORDERING INFORMATION

Description	Order Code
High current loop tester with red/green lead set	LT300-EN-00
High current loop tester with BS1363 mains plug lead	LT300-EN-BS
High current loop tester complete with fused leads	LT300-EN-FS
Included Accessories	
Red/green 2 wire test lead set (LT300-EN-00)	1001-976
Mains plug test lead (BS1363) (LT300-EN-BS)	6220-810
Hard carry case	5410-409
Fused leads ONLY WITH LT300-EN-FS	1001-977
Optional Accessories	
Mains plug test lead (BS1363) (LT300-EN-BS)	6220-810
Red/green 2 wire test lead set (LT300-EN-00)	1001-976
Spare fuse for leads	25950-013

UK
Archcliffe Road Dover
CT17 9EN England
T +44 (0) 1304 502101
F +44 (0) 1304 207342
UKsales@megger.com

UNITED STATES
4271 Bronze Way
Dallas TX 75237-1019 USA
T 800 723 2861 (USA only)
T +1 214 333 3201
F +1 214 331 7399
USsales@megger.com

OTHER TECHNICAL SALES OFFICES
Valley Forge USA, College Station USA,
Sydney AUSTRALIA, Täby SWEDEN, Ontario
CANADA, Trappes FRANCE, Oberursel GER-
MANY, Aargau SWITZERLAND, Kingdom of
BAHRAIN, Mumbai INDIA, Johannesburg
SOUTH AFRICA, Chonburi THAILAND

CERTIFICATION ISO
Registered to ISO 9001:2000 Cert. no. Q 09290
Registered to ISO 14001:1996 Cert. no. EMS 61597
LT300_HI_DS_en_V04
www.megger.com
Megger is a registered trademark