



### MATERIALS:

Shielded Housing: Extruded Aluminum, Alloy 6063-ST  
 Finish: Blue baked enamel per Federal Standard 595,  
 #25109 over primer wash per DOD-P-15328.  
 Cover: 2 each, 2.03 (.080) thick Aluminum, Alloy  
 1100-H14

Finish: Clear anodized per MIL-A-8625

Screws: 16 each #4-40 x 6.35 (1/4") Flat head with  
 blue zinc plating

### RATINGS:

Operating Temperature: +150°C (+302°F) Max.

### ORDERING INFORMATION: Model 3311

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).  
 All specifications are to the latest revisions. Specifications are subject to change without notice.  
 Registered trademarks are the property of their respective companies.

Made in USA

6/9/99

SY/EH/LS

S:\Engineering\Release\DataSheets\FI\ukeDataSheet\3311\_1\_01.doc

Sales: 800-490-2361 Fax: 888-403-3360  
 Technical Assistance: 800-241-2060

PomonaACCESS 90188 (800) 444-6785 or (425) 446-6010  
 More drawings available at [www.pomonaelectronics.com](http://www.pomonaelectronics.com)

Page 1 of 1