



FEATURES:

- Converts BNC (Male) cables to stackable miniature banana plugs for test versatility
- BNC and banana plugs are molded directly onto the wire for pull strength durability and dust and moisture resistance
- BNC center contact and miniature banana plug springs are gold plated Beryllium Copper for corrosion resistance, low contact resistance and long insertion life

MATERIALS:

BNC: Nickel-plated Brass

Center Contact – Gold plated Beryllium Copper

Wire: 20 AWG, PVC

Marking: “POMONA 3966”

Miniature Banana Plugs: Gold plated brass

Spring: Gold plated Beryllium Copper

Insulation: Polypropylene color: red to BNC center contact, black to BNC shell

RATINGS:

Operating Voltage: Hand-Held testing: 30VAC/60VDC Max.

Hands free testing in controlled voltage environments: 500VRMS Max.

Operating Temperature: +55°C (+131°F) Max.

ORDERING INFORMATION: Model 3966

All dimensions are in inches.

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

Sales: 800-490-2361 Fax: 888-403-3360
Technical Assistance: 800-241-2060

PomonaACCESS 90337 (800) 444-6785 or (425) 446-6010
More drawings available at www.pomonaelectronics.com