


## Model 4280 and 4280N WE=310 (PJ-051) To Bantam Miniature Phone Plug



### FEATURES:

- Shielded cable to reduce noise
- WE-310 and Bantam Plugs molded to the cable for optimum durability

### MATERIALS:

Plugs – (4280) Brass, unplated

(4280N) Brass, nickel plated

Cable – 2 Conductor shielded twisted pair, PVC jacket and insulation

### RATINGS:

Operating Voltage: 300 VRMS Max.

Operating Temperature: +50°C to (+122°F) Max.

Current: 3.36 Amperes @ 25°C

Nominal Capacitance Shield Conductors: 720pf

Nominal Capacitance Between Conductors: 420pf

### ORDERING INFORMATION: XX = Length in inches

Model 4280-XX Standard Lengths 48" (1219 mm), 60" (1520 mm)

4280N-XX Standard Lengths 36" (914 mm)

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

10/01/07

Sales: 800-490-2361 Fax: 425-446-5844  
Technical Support: [technicalsupport@pomonatest.com](mailto:technicalsupport@pomonatest.com)

D1094048  
Rev. 101

[www.pomonaelectronics.com](http://www.pomonaelectronics.com)  
Page 1 of 1