



FEATURES:

- Converts BNC (male) cables/connectors to #8 spade lugs for terminal strip attachment
- BNC connector is molded directly to the wire for pull strength durability and dust and moisture resistance
- BNC shell is tarnish resistant
- BNC center contact is gold plated Beryllium Copper for excellent electrical connection
- Black wire is connected to BNC shell, red wire to BNC center contact

MATERIALS:

BNC: Nickel-plated Brass

Center Contact: Gold plated Beryllium Copper

Wire: 20 AWG, PVC

Marking: "POMONA 5051"

#8 Spade Lug: Tin-plated copper alloy

Insulation: Vinyl, color: one red, one black

RATINGS:

Operating Voltage: Hand-held testing: 30VAC/60VDC Max.

Hands free testing in controlled voltage environments: 500VRMS Max.

Operating Temperature: +55°C (+131°F) Max.

ORDERING INFORMATION: Model 5051

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

Sales: 800-490-2361 Fax: 888-403-3360
Technical Assistance: 800-241-2060

PomonaACCESS 90432 (800) 444-6785 or (425) 446-6010
More drawings available at www.pomonaelectronics.com