



FEATURES:

- Converts BNC (Male) cables to .025" (.635mm) receptacles for attachment to square pins on test boards, etc.
- BNC connector is molded directly to the wire for pull strength durability and dust/moisture resistance.
- BNC center contact is gold plated Beryllium Copper and receptacle is gold plated for noise free electrical connection.
- Schematic: Red receptacle to BNC center contact, Black receptacle to BNC shell.

MATERIALS:

BNC: Body - Brass, Nickel Plated

Center Contact – Beryllium Copper, Gold Plated.

Wire: 22 AWG, Stranding 19 x 34 T.C., PVC Insulated, .064" (1.63mm) O.D., Color: One black, one red

Marking (Black Wire Only): "POMONA 5069"

Receptacle: Body: Phosphor Bronze, Gold Plated

ABS, Color matches color of wire

RATING:

Voltage: Hand-held testing: 30VAC/60VDC Max.

Hands free testing in controlled voltage environments: 500VRMS Max.

Operating Temperature: +50°C (+122°F) Max.

ORDERING INFORMATION: Model 5069

All dimensions are in inches and metric. All specifications are to the latest revisions. Specifications are subject to change without notice.
Registered trademarks are the property of their respective companies. Made in USA

Sales: 800-490-2361 Fax: 888-403-3360
Technical Assistance: 800-241-2060

PomonaACCESS 90455 (800) 444-6785 or (425) 446-6010
More drawings available at www.pomonaelectronics.com