

## Model 5088 SMA Male Shorting Plug



## **FEATURES:**

• Protects sensitive instrument inputs or provides a necessary reference short.

## **MATERIALS:**

Body and Fittings: Steel per QQ-S-764, Type 303, cond. A

Center Contact: Gold Plated Steel per QQ-S-764, Type 303, cond. A Gaskets and Seals: Silicone rubber per ZZ-R-765, Class II, Grade 65-75.

Finish:

Body and Fittings: Gold plated steel per requirements of MIL-C-39012 Center Contact: Gold plated steel per requirements of MIL-C-39012

**ORDERING INFORMATION:** Model 5088

All dimensions are in inches. Tolerances (except noted):  $.xx = \pm .02$ " (,51 mm),  $.xxx = \pm .005$ " (,127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies. Made in USA

7/1/02 SY/EH/LS LG d5088\_1\_02 Sales: 800-490-2361 Fax: 888-403-3360 Technical Assistance: 800-241-2060 Pomona*ACCESS* **90297** (800) 444-6785 or (425) 446-6010 More drawings available at www.pomonaelectronics.com

C:\Laura Goldberg\FlukeDataSheet\d5088\_1\_02.doc