



FEATURES:

- High temperature insulation material for use up to 220°C (428°F).
- Mates with Pomona's MDP and all standard double banana plugs.
- Ideal for mounting to panels or chassis boxes.

Banana Jack Body/Solder Turret – Material: H.H. per QQ-B-626, Alloy 360, ½ Hard.
Finish: Bright tin plated per MIL-T-10727.

RATINGS:

Operating Temperature: +220°C. (+428°F.) Max.
Operating Voltage: 2500 VDC
Current: 15 Amperes. Cont.

ORDERING INFORMATION: Model 5233-*
*=Color, -0 Black (has one Black and one Blue Jack)
Ordering Example: 5233-0, Color is Black

MATERIALS:

Banana Jack Insulation: Polyphenylene Sulfide molded to Banana Jack Bodies.

Color: One Blue, One Black.

Mounting Plate: Polyphenylene Sulfide.

Color: Black

Insulator: Polyphenylene Sulfide. Color matches color of Banana Jack insulation.

Hex Nut ¼-32: Material Brass

Nickel plated. Class 2, 200/300 micro-inches.

Lockwasher ¼ Int Tooth: Material: Steel.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

Made in USA