



FEATURES:

- Ideal for providing a temporary jumper wire between surface mount devices.

MATERIALS:

SMD Grabber® test clip

Contact - Stainless Steel

Spring - Stainless Steel

Cap - Glass filled nylon. Color matches color of wire

Barrel - Glass filled nylon. Color matches color of wire

Marking: "POMONA GRABBER®"

Finish: Gold plated

Wire: 22 AWG, PVC insulated

Marking: "Model 5301"

RATINGS:

Operating Temperature: $+102^{\circ}\text{C}$ ($+216^{\circ}\text{F}$) Max.

Voltage: Hand-held testing 33 Vrms/70 Vdc Max.

Hands free testing in controlled voltage environments: 150 WVDC Max.

Current: .5 Amperes

ORDERING INFORMATION: Model 5301-XX-*

XX = Standard Lengths in Inches, 12" and 24"

* = Color, -0 Black, -2 Red

Ordering Example: 5301-12-2 Indicates 12", color is red.

5521 Kit contains 10 pieces of model 5301-24, 1 each of 10 colors.

All dimensions are in inches. Tolerances (except noted): $.xx = \pm .02"$ ($.51$ mm), $.xxx = \pm .005"$ ($.127$ mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.