

# Technical Data Sheet

### Models 7158 , 7159, 7160 1/4" 2 & 3-Cond. Phone Jack, PC Board Mount



Model 7158 Horizontal 3-Conductor Jack, PC Board Mount

#### **Ordering Information**

Model: 7158, 7159, 7160



Model 7159 Horizontal 2-Conductor Jack, PC Board Mount



Model 7160 Horizontal 3-Conductor Jack, Solder Tabs

# Use to mount securely with PC boards.

#### **Features**

- Connects with standard commercial phone plugs
- PC board mountable
- Stereo and mono versions
- Solderable
- 2 and 3 conductor versions

#### **Materials**

- Shell: Polyamide 6.6 15% GR
- Contacts: Nickel silver

 USA:
 Sales:
 800-490-2361
 Technical Support:
 800-241 

 2060
 Fax:
 888-403-3360
 International:
 425-446-5500

 e-mail:
 technicalsupport@pomonatest.com
 International:
 425-446-5500

Where to Buy: www.pomonaelectronics.com

# Specifications

Number of conductors	2 (Mono)-Model 7159 3 (Stereo)-Models 7158, 7160
Contact resistance	< 15 mΩ
Dielectric strength	1000 V dc
Insulations Resistance	1000 ΜΩ

All dimensions are in inches. Tolerances (except noted):  $.xx = \pm .02^{\circ}$  (,51 mm),  $.xxx = \pm .005^{\circ}$  (,127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

# www.valuetronics.com