



| MODEL NO. | * RESISTANCE VALUE Ω |
|-----------|-----------------------------|
| 4119-50 | 50 |
| 4119-75 | 75 |
| 4119-93 | 93 |
| 4119-600 | 600 |

MATERIALS:

Body and Fittings: Brass, Alloy 360, 1/2 Hard.

Center Contact: Male – Brass, Alloy 360, 1/2 Hard.

Female – Beryllium Copper per Cond. Ht.

Outer Contact: Beryllium Copper, Cond. Ht.

Dielectric: Teflon per L-P-403.

Gasket/Seals: Silicone rubber per zz-r-765, Class 11a, Grade 50.

Finish:

Body and Fittings: Tarnish Resistant.

Center Contact: Male – Gold plated.

Outer Contact: Tarnish Resistant.

Marking: "Pomona Elect. 4119-*" and resistance value marked on label.

Specifications: 2%, 2 Watt, Carbon-film resistor deposited over Ceramic Core.

VSWR: 1.1 Max. from D.C. to 250 MHz.

1.2 Max. from 250 MHz to 500 MHz.

RATINGS:

Operating Temperature: +102°C (+216°F) Max.

ORDERING INFORMATION: Model 4119-*

* = Resistance value (see table above)

All dimensions are in inches. Tolerances (except noted): .xx = ± 0.02 " (.51 mm), .xxx = ± 0.005 " (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

6/9/99

SY/EH/LS

S:\Engineering\Release\DataSheets\FI\ukeDataSheet\4119_1_01.doc

Sales: 800-490-2361 Fax: 888-403-3360

Technical Assistance: 800-241-2060

PomonaACCESS 90228 (800) 444-6785 or (425) 446-6010

More drawings available at www.pomonaelectronics.com

Page 1 of 1