

Guardian 6000 Plus

Electrical Safety Analyzer with Revolutionary Twin Port Technology

USES:

- Production and Compliance Testing of Appliances, Instruments and Information Technology Equipment in Accordance with UL, CSA, IEC, TUV and Other Standards such as EN60335, EN60950, EN61010, CSA C22.2 No. 1010.1, UL3111 and UL60950
- Transformer Electrical Safety Testing
- Electric Motor Safety Testing
- Power Supply Safety Testing
- Verification of the Ground Connection on Products with a Three Prong Power Cord

FEATURES:

- Twin Port - Simultaneous Hipot & GB
- Programmable Output Voltage to 5KV AC and 6KV DC
- Ground Bond Testing to 30A AC (to 40A with Optional Transformer)
- Insulation Resistance Measurements from 100k Ω to 50G Ω
- Open/Short Circuit Detection Mode
- Programmable Ramp, Dwell & Test Times
- Storage of 100 Test Setups, 50 Steps Each
- Continuous Leakage Current Monitoring
- Programmable Trip Current to 40mA AC and 12mA DC
- Front Panel Lockout via Password
- Standard RS-232 & Remote I/O Interfaces
- Optional IEEE-488, Printer Interfaces
- Optional Built-in 8 Channel Scanner
- Optional CaptivATE Automation Software for G6000 Plus

Introduction

The Guardian 6000 Plus is the industry's first safety analyzer with simultaneous Hipot and Ground Bond capability providing a dramatic savings in test time. Five instruments in one, the G6000 Plus provides AC Hipot, DC Hipot, Insulation Resistance, Ground Bond and Open/Short measurements from a single test connection. Versatile and packed with features, the G6000 Plus is a cost effective solution to the full spectrum of electrical safety compliance testing.

Description

AC Hipot: AC dielectric testing over the voltage range from 50V to 5000VAC RMS. The maximum leakage current of 40mA RMS is ideal for testing devices with high leakage currents such as power supplies which have large filter or "Y" capacitors for noise reduction.

DC Hipot: DC dielectric testing from 50V to 6000VDC with a resolution of 1V. Leakage current can be continuously monitored from 0.1 μ A to 12mA DC.

Insulation Resistance: The G6000 Plus is capable of measuring IR from 100k to 50G Ω with test voltage from 50V to 1000VDC in 1V steps.

Quick Discharge: In both DC and IR modes, the device under test is discharged through the HV transformer resulting in a rapid and safe discharge.

Ground Bond: With test current from 1A to 30A in 0.1A steps and programmable current limits, test time, frequency and open circuit no load voltage, the G6000 Plus provides full GB testing capability. The offset feature automatically compensates for any lead resistance. A 40A GB option is also available.

Twin Port Technology: This patented feature allows for simultaneous Ground Bond and Hipot Testing. Decrease test time and increase device throughput.

Open/Short Circuit Detection Mode: Check for Opens and Shorts against a standard capacitance value, Cs, and have confidence the DUT is properly connected.

Optional Scanners: One internal and/or multiple external scanners may be added to the G6000 Plus for testing multiple devices simultaneously. Add up to 8 HV channels or a combination of HV and GB channels.

Standard Interfaces: The Remote I/O and RS-232 interfaces provide remote control and serial data collection capability for automated applications.



For more detailed information on specifications, pricing and special purchase, rent and lease options, contact us at:

www.quadtech.com

800-253-1230



Hipot Testers • LCR Meters • Cable Testers • AC/DC Programmable Power Sources
• Megohmmeters • Milliohmmeters

Guardian 6000 Plus

AC Output Voltage:	Range: 50V to 5000V AC, 1V resolution Regulation: <(1% of setting +5V) at Rated Load Freq: 50-600 Hz, programmable in 1Hz steps 50~60Hz : 1% + 5 cnts, > 60Hz: 3%+10 cnts Waveform: Sinusoidal
Voltage Display:	Accuracy: ±(1% of reading + 5V) Resolution: 1Volt
AC Current Display:	Total current Range: 0.001 to 40mA AC Resolution: 1 or 10µA steps Accuracy: ±(1% of reading + 5cnt)
High/Low Limit Test:	1µA to 40mA AC Low limit can be turned OFF
Arc Detection:	Programmable 1-20mA, Pulse Width 40µ, 20µ, 10µ or 4µsec
DC Output Voltage:	Range: 50V to 6000V DC, 1V resolution Regulation: <(1% +5V) at Rated Load
Voltage Display:	Accuracy: ±(1% of reading + 5V) Resolution: 1Volt
DC Current Display:	Range: 0.1µ to 12mA DC Resolution: 0.1, 1 or 10µA steps Accuracy: ±(1% or reading + 5cnt)
High/Low Limit Test:	0.0001mA to 12mA DC Low limit can be turned OFF
Arc Detection:	Programmable 1-10mA Pulse Width 40µ, 20µ, 10µ or 4µsec
Insulation Resistance:	Range: 50V - 1000V DC Accuracy: ±5% to ±15% depending upon voltage and resistance
Voltage Range:	100kΩ - 50GΩ
Voltage Display:	±(1% of reading + 5V)
High/Low Limit Test:	100kΩ - 50GΩ Low limit can be turned OFF
Ground Bond:	
Output Current:	Range: 1.0 to 30.0A AC, setting .01A/step; *40A Regulation: ±(1% of setting + 0.3A) Accuracy: ±(1% of reading + 3 counts)
Frequency:	50 or 60Hz Selectable
No Load Voltage:	6 to 15 V Programmable
Resistance:	Range: 0.1mΩ - 510mΩ, 4 digits Accuracy: ±(1% of reading + 3 counts) Resolution: 0.1mV
High Limit:	0.1mΩ to 510mΩ
Start Wait:	0.1 - 99.9sec

*GB to 40A with optional transformer

Common Features:

Open/Short Circuit Mode:	Check for Open & Short against a standard capacitance value (Cs); <100V, 600Hz
Offset Function:	0 to 100mΩ offset, user selectable AC Programmable Offset, 0-25mA
Test Time:	Ramp: 0.3 to 999s (±20ms), (AC/DC/IR) Dwell: 0 to 999s (±20ms), (DC only) Start Wait: 0.1 to 99.9s (±20ms), (GB only) Test: 0.3 to 999s (±20ms) or Continuous (ALL) Ramp, Dwell & Start Wait can be set to OFF
Remote Control:	Inputs: Start, Stop Characteristics: Optically Isolated, Low, Pulse Width >1ms. Outputs: Pass/Fail/Under Test Characteristics: Dry Contact relay Electrical Characteristics: 120V 100mA max. Logic: Closed if True Connector: Terminal Strip and 9 pin D Series
Test Setups:	100 Test Setups with 50 Steps each, 13 character Alpha-Numeric Label
Connectors:	Front and Rear 4- terminal connection
Display:	320 x 240 enhanced LCD with status indicators
Front Panel Lockout:	Key Lock with Password Fail Lock with Password
Safety Features:	Fast Cutoff (<0.4ms) & Fast Discharge (0.2s) Adjustable Discharge: .05-5.1kV DC
Miscellaneous:	Fail Retest; Continue on Fail PAUSE Mode: Program pause between steps
Indication:	Pass/Fail lights, audible sound; Remote, Lock, Offset & Error status indicators
Buzzer Level:	1,2,3 and Off
Standard Interfaces:	RS-232, Remote I/O Data bits: 8, Stop bits: 1; Parity: None Selectable Baud Rate: 300 - 19200
Optional Interfaces:	IEEE-488, Printer
Dimensions:	(w x h x d):17x5.25x18.5in (430x133x470mm)
Weight:	53 lbs (24kg) - Net, 60 lbs (27kg) Shipping
Environmental:	Operating: 0 to + 40° C, Humidity: <75% Storage: - 20 to + 70° C Warm-up Time: 1minute
Power:	• 90 - 130V AC • 50 or 60Hz • 200 - 250V AC • 800W max

Ordering Information

Guardian 6000 Plus Electrical Safety Analyzer	Optional Accessories	G13 Corded Product Adapter (115V)
Includes:	N/A Calibration Data	G14 Power Entry Adapter
150798 Instruction Manual	6000-01 Scanner, 8 Channel 5HV,3GC	G16 International Power Strip
S02 HV Lead Set, 1m	6000-02 Scanner, 8 Channel 3HV,5GC	G24 Scanner Cable (5000 scanners)
G15 Ground Continuity Lead Set	6000-03 Scanner, 8 Channel HV	G25 Corded Product Adapter (240V)
G14 Power Entry Adapter	S04 HV Lead Set 2m	G38 Printer Interface (replaces IEEE)
4200-0300 AC Power Cable	S05 Foot Switch	G39 IEEE-488 Interface
520157 8A 250V Power Line Fuse	S08 Gun Probe	G43 Rack Mount Kit
520053 4A 250V Power Line Fuse	S09 HV Lead, 1M, Unterminated	G44 Barcode Scanner
N/A Calibration Cert. Traceable to NIST	S10 HV Lead, 1M, Unterminated	G45 40A Ground Bond Transformer

For more detailed information on specifications, pricing and special purchase, rent and lease options, contact us at:

www.quadtech.com or 800-253-1230