

MG100S 110-240 V

Product no.: U-100-1000-ESDN



Benefits

- › H13 particle filter and wide band gas filter
- › Electronic filter control with filter alarm
- › 3-speed setting
- › Compact footprint
- › Switching power supply 100 - 240 V
- › Optimized filter lifetime
- › Applications: Hand soldering, heavy duty and general soldering, gluing, cleaning, filling, and fine dust
- › Can be equipped with optional filter for MEK, VOC, and cleanroom applications
- › Includes MG100S fume extraction unit 120V / 50/60 Hz with H13 particle filter with wide band gas filter



Technical Data

| | |
|----------------------------------|---|
| Dimensions L x W x H (mm) | 460 x 210 x 610 |
| Dimensions L x W x H (inches) | 18.11 x 8.26 x 24.15 |
| Weight (approx.) in kg | 15 |
| Voltage | 110 - 240 V, 50/60 Hz |
| Power | 100 W |
| Noise level (distance 1 m) dB(A) | < 52 |
| Max. vacuum | 2300 Pa |
| Capacity m ³ /h | 140 |
| Pre-filter | --- |
| Compact filter | Particle filter H13, Wide band gas filter (50 % Active carbon + 50 % Chemisorb) |
| Max. capacity | 1-2 workstations |
| RS232 interface (remote control) | --- |
| USB port | --- |
| WX-compatible | --- |